

ATEN CL1308N, US KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: CL1308N-ATA-2XK06A1G

Tuotteen nimi: CL1308N, US

ATEN CL1308N, US. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2.

Enimmäiserottelutarkkuus: 1280 x 1024 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19").

Tulojännite: 100-240 V, AC-syöttötaajuus: 50 - 60 Hz, Syöttöjännite: 1 A

Ports & interfaces		Power	
Number of computers controlled * Keyboard port type * Mouse port type *	8 USB, PS/2 USB, PS/2	AC input frequency Input current Power consumption (typical)	50 - 60 Hz 1 A 22 W
Performance		System requirements	
Maximum resolution * Scan interval DDC2B support	1280 x 1024 pixels 1,255 s	Windows operating systems supported Linux operating systems supported	✓ ✓
Hot-swap	✓	Sustainability	
Design		Compliance certificates	RoHS
Rack mounting *	✓	Operational conditions	
Rack capacity Product colour * Housing material	1U Black Metal, Plastic	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 50 °C -20 - 60 °C 0 - 80%
LED indicators	✓	Weight & dimensions	
Push button Keyboard language	✓ US English	Width Depth	689.2 mm 483 mm
Display		Height	44 mm
Built-in display * Display	✓ LCD	Weight Packaging content	12.6 kg
Display diagonal On Screen Display (OSD)	48.3 cm (19")	Manual	/
Power		Logistics data	85176200
Input voltage	100-240 V	Harmonized System (HS) code	031/0200

