ATEN

ATEN CL5708IN-ATA-2XK06FG KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: CL5708IN-ATA-2XK06FG

Tuotteen nimi: CL5708IN-ATA-2XK06FG

ATEN CL5708IN-ATA-2XK06FG. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Tietoturva-algoritmit: 128-bit RC4, RSA, SSL/TLS. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19")





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type *	8 USB, PS/2 USB, PS/2 VGA	Built-in display * Display Display diagonal On Screen Display (OSD)	✓ LCD 48.3 cm (19") ✓
Console ports * Console USB ports quantity	RJ-45, USB A, VGA (D-Sub) 1	Power	
USB connector type	USB Type-A	Power source	AC
Network Ethernet LAN (RJ-45) ports Security algorithms	1 128-bit RC4, RSA, SSL/TLS	Input voltage AC input frequency Input current	100-240 V 50 - 60 Hz 1 A
Performance		System requirements	
HD type * WUXGA Maximum resolution * 1920 x 1200 pix Scan interval 1,255 s	1920 x 1200 pixels	Windows operating systems supported Linux operating systems supported Mac operating systems supported	<i>y y</i>
DDC2B support	✓	Operational conditions	
HDCP Hot-Plug support Daisy chain	✓ ✓	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 50 °C -20 - 60 °C 0 - 80%
Power on detection	✓	Weight & dimensions	
Pesign Rack mounting * Rack capacity	7 10	Width Depth Height Weight	689.2 mm 480 mm 44 mm 13.4 kg
Product colour *	Black	Packaging content	
Housing material Metal, Plastic LED indicators Display switch button Push button Hot keys Keyboard language French	* * *	Cables included Manual Rack mount kit	AC, KVM

