## **ATEN**

## ATEN L5708IM-ATA-2XK06FG KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: CL5708IM-ATA-2XK06FG

Tuotteen nimi: L5708IM-ATA-2XK06FG

ATEN L5708IM-ATA-2XK06FG. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Tietoturva-algoritmit: 128-bit RC4, RSA, SSL/TLS. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Näyttö: LCD, Näytön halkaisija: 43,2 cm (17")





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type *	8 USB, PS/2 USB, PS/2 VGA	Built-in display * Display Display diagonal On Screen Display (OSD)	✓ LCD 43.2 cm (17")
Console ports * Console USB ports quantity	RJ-45, USB A, VGA (D-Sub) 1	Power	
USB connector type	USB Type-A	Power source	AC
Network		Input voltage	100-240 V 50 - 60 Hz
Ethernet LAN (RJ-45) ports Security algorithms	1 128-bit RC4, RSA, SSL/TLS	AC input frequency Input current	1 A
, 5	120-bit RC4, R3A, 33L/1L3	System requirements	
Performance  HD type *	WUXGA	Windows operating systems supported	✓
Maximum resolution *	1920 x 1200 pixels	Linux operating systems supported	✓
Scan interval	1,255 s	Mac operating systems supported	✓
DDC2B support	<b>✓</b>	Operational conditions	
HDCP	<b>V</b>	Operating temperature (T-T)	0 - 50 °C
Hot-Plug support  Daisy chain	<b>V</b>	Storage temperature (T-T)	-20 - 60 °C
Power on detection	<b>v</b>	Operating relative humidity (H-H)	0 - 80%
Firmware upgradeable	,	Weight & dimensions	
Design	•	Width	642.7 mm
•	,	Depth Height	480 mm 44 mm
Rack mounting *  Rack capacity	<b>√</b> 1U	Weight	13.5 kg
Product colour *	Black	Packaging content	
Housing material	Metal, Plastic	Cables included	AC. KVM
LED indicators	✓	Manual	<b>✓</b>
Display switch button	✓	Rack mount kit	<b>✓</b>
Push button	✓		
Hot keys	✓		

