## **ATEN**

## ATEN CL5708M KVM switch Rack mounting Black

Brand: ATEN Product code: CL5708M-ATA-2XK06UG

Product name: CL5708M

17" LED-backlit LCD KVM Switch

## ATEN CL5708M KVM switch Rack mounting Black:

The CL5708 Slideaway™ LCD KVM Switch is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5708 can control up to 8 computers. As many as 31 additional KVM switches can be daisy-chained to the CL5708, so that up to 256 computers can all be controlled from a single KVM console.

The CL5708 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17" or 19" LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing. ATEN CL5708M. Mouse port type: USB, USB connector type: USB Type-A. Maximum resolution: 1280 x 1024 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Housing material: Metal, Plastic. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Input current: 1 A





Ports & interfaces		Power	
Number of computers controlled *	8	Input current	1 A
Mouse port type *	USB	Power consumption (typical)	16 W
USB connector type	USB Type-A	System requirements	
Performance		Windows operating systems	/
Maximum resolution *	1280 x 1024 pixels	supported	•
Scan interval	1,255 s	Linux operating systems supported	✓
DDC2B support	✓	Mac operating systems supported	✓
Hot-swap	✓	Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
Rack mounting *	<b>✓</b>	Storage temperature (T-T)	-20 - 60 °C
Rack capacity	10	Operating relative humidity (H-H)	0 - 80%
Product colour *	Black	Weight & dimensions	
Housing material	Metal, Plastic	Width	642.7 mm
LED indicators	✓	Depth	480 mm
Display		Height	44 mm
Built-in display *	<b>✓</b>	Weight	13.5 kg
Display	LCD	Packaging content	
Display diagonal	43.2 cm (17")	Manual	1
On Screen Display (OSD)	✓	Logistics data	
Power		Harmonized System (HS) code	85176200
	100-240 V		552, 5200
Input voltage AC input frequency	100-240 V 50 - 60 Hz		
AC IIIput ITEquelicy	JU - UU IIZ		

