



## ATEN CL5716M-ATA-2XK06ITG KVM switch Rack mounting Black



**Brand :** ATEN

**Product code:** CL5716M-ATA-2XK06ITG

**Product name :** CL5716M-ATA-2XK06ITG

16 Port 17" LCD KVMP Switch

[ATEN CL5716M-ATA-2XK06ITG KVM switch Rack mounting Black:](#)

The CL5716 Slideaway™ LCD KVM Switch is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5716 can control up to 16 computers. As many as 31 additional KVM switches can be daisy-chained to the CL5716, so that up to 512 computers can all be controlled from a single KVM console.

The CL5716 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17" or 19" LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing. ATEN CL5716M-ATA-2XK06ITG. Mouse port type: USB. Maximum resolution: 1280 x 1024 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Housing material: Metal, Plastic. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Input current: 1 A

Ports & interfaces		Power	
Number of computers controlled *	16	AC input frequency	50 - 60 Hz
Mouse port type *	USB	Input current	1 A
<b>Performance</b>		Power consumption (typical)	18 W
Maximum resolution *	1280 x 1024 pixels	<b>System requirements</b>	
Scan interval	1,255 s	Windows operating systems supported	✓
DDC2B support	✓	Linux operating systems supported	✓
Hot-swap	✓	Mac operating systems supported	✓
<b>Design</b>		<b>Operational conditions</b>	
Rack mounting *	✓	Operating temperature (T-T)	0 - 40 °C
Rack capacity	1U	Storage temperature (T-T)	-20 - 60 °C
Product colour *	Black	Operating relative humidity (H-H)	0 - 80%
Housing material	Metal, Plastic	<b>Weight &amp; dimensions</b>	
LED indicators	✓	Width	642.7 mm
<b>Display</b>		Depth	480 mm
Built-in display *	✓	Height	44 mm
Display	LCD	Weight	13.6 kg
Display diagonal	43.2 cm (17")	<b>Packaging content</b>	
On Screen Display (OSD)	✓	Manual	✓
<b>Power</b>			
Input voltage	100-240 V		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date