



ATEN CS1716I-AT-G KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: CS1716I-AT-G

Tuotteen nimi : CS1716I-AT-G

ATEN CS1716I-AT-G. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Tietoturva-algoritmit: 128-bit RC4, SSL/TLS. HD-tyyppi: QXGA, Enimmäiserottelutarkkuus: 2048 x 1536 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metallii. Voimanlähde: DC, Tulojännite: 5.3 V, Virrankulutus: 11 W



Ports & interfaces		System requirements	
Number of computers controlled *	256	Windows operating systems supported	✓
Keyboard port type *	USB, PS/2	Linux operating systems supported	✓
Mouse port type *	USB, PS/2	Mac operating systems supported	✓
Video port type *	VGA		
VGA (D-Sub) ports quantity	16		
Console ports *	USB A, VGA (D-Sub)		
Console USB ports quantity	1		
Network		Sustainability	
Ethernet LAN	✓	Compliance certificates	RoHS
Ethernet LAN (RJ-45) ports	1		
Security algorithms	128-bit RC4, SSL/TLS		
Performance		Operational conditions	
HD type *	QXGA	Operating temperature (T-T)	0 - 50 °C
Maximum resolution *	2048 x 1536 pixels	Storage temperature (T-T)	-20 - 60 °C
Video bandwidth	60 Hz	Operating relative humidity (H-H)	0 - 80%
Scan interval	1,255 s		
DDC2B support	✓		
HDCP	✓		
Hot-Plug support	✓		
Daisy chain	✓		
Number of users	32 user(s)		
Firmware upgradeable	✓		
Design		Weight & dimensions	
Rack mounting *	✓	Width	437.2 mm
Rack capacity	1U	Depth	159.6 mm
Product colour *	Black	Height	44 mm
Housing material	Metal	Weight	3.59 kg
LED indicators	✓		
Push button	✓		
Hot keys	✓		
Display		Packaging data	
Built-in display *	✗	Package width	116 mm
		Package depth	540 mm
		Package height	233 mm
		Package weight	3.98 kg
		Packaging content	
		Cables included	DC, KVM
		Quick installation guide	✓
		Manual	✓
		AC adapter included	✓
		Software included	✓
		Rack mount kit	✓
		Logistics data	
		Master (outer) case net weight	10.8 kg
		Harmonized System (HS) code	85176200
		Master (outer) case width	375 mm
		Master (outer) case length	565 mm

Display		Logistics data	
On Screen Display (OSD)	✓	Master (outer) case height	258 mm
Power		Master (outer) case gross weight	12.6 kg
Power source	DC	Products per master (outer) case	3 pc(s)
Input voltage	5.3 V		
Power consumption (typical)	11 W		



4710423776722

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date