## **ATEN**

## ATEN CL6700MW-ATA-2XK07GG KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: CL6700MW-ATA-2XK07GG

Tuotteen nimi : CL6700MW-ATA-2XK07GG

ATEN CL6700MW-ATA-2XK07GG. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, USB-liitin: USB Atyyppi, USB B-tyyppi. HD-tyyppi: Full HD, Enimmäiserottelutarkkuus: 1920 x 1080 pikseliä. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Näyttö: LCD, Näytön halkaisija: 43,9 cm (17.3"). Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz, Syöttöjännite: 1 A



Ports & interfaces		Power	
Number of computers controlled * Keyboard port type * Mouse port type * HDMI ports quantity DVI-D ports quantity	1 USB USB 2 2	Input voltage AC input frequency Input current Power consumption (typical) System requirements	100 - 240 V 50 - 60 Hz 1 A 19.4 W
VGA (D-Sub) ports quantity USB connector type	2 USB Type-A, USB Type-B	Windows operating systems supported	1
Performance		Linux operating systems supported	1
HD type *	Full HD	Mac operating systems supported	1
Maximum resolution *	C/DDC2 supported	Sustainability	
BB6/BB62 Supported		Compliance certificates	RoHS
DDC2B support		Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
<b>Design</b> Rack mounting * Rack capacity	✓ 1U	•	0 - 40 °C -20 - 60 °C 0 - 80%
Rack mounting * Rack capacity Product colour *	1U Black	Operating temperature (T-T) Storage temperature (T-T)	-20 - 60 °C
Rack mounting * Rack capacity Product colour * Housing material LED indicators Keyboard language	10	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 60 °C
Rack mounting * Rack capacity Product colour * Housing material LED indicators	1U Black Metal	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth	-20 - 60 °C 0 - 80% 589.2 mm 480 mm
Rack mounting * Rack capacity Product colour * Housing material LED indicators Keyboard language	1U Black Metal	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height	-20 - 60 °C 0 - 80% 589.2 mm 480 mm 44 mm

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.