



## ATEN CL6700MW-ATA-2XK06UG KVM switch Rack mounting Black

**Brand :** ATEN

**Product code:** CL6700MW-ATA-2XK06UG

**Product name :** CL6700MW-ATA-2XK06UG

USB DVI WideScreen Full HD LCD Console with USB, UK

[ATEN CL6700MW-ATA-2XK06UG KVM switch Rack mounting Black:](#)

The CL6700MW DVI Full HD LCD Console is a single rail KVM console featuring a 17.3" LED-backlit high-definition widescreen with an integrated keyboard and touchpad in a 1U rack-mountable sliding housing. The CL6700MW's console provides front end access to compatible KVM switches utilizing space with a module that closes flat and slides into the rack. The single rail design allows the LCD monitor, keyboard and touchpad to operate independently of each other. Multiple video ports allow the console to connect one of three types of video sources: VGA, DVI, or HDMI - for the console and CPU connection. For added convenience, the full HD console provides two HDMI ports that allow for connecting a high-definition monitor to the console port, and/or an HDMI compatible switch to the KVM port.



Ports & interfaces		Power	
Number of computers controlled *	1	AC input frequency	50 - 60 Hz
Keyboard port type *	USB	Input current	1 A
Mouse port type *	USB	Power consumption (typical)	19.4 W
HDMI ports quantity	2	<b>System requirements</b>	
DVI-D ports quantity	2	Windows operating systems supported	✓
VGA (D-Sub) ports quantity	2	Linux operating systems supported	✓
USB connector type	USB Type-A, USB Type-B	Mac operating systems supported	✓
Performance		Sustainability	
HD type *	Full HD	Compliance certificates	RoHS
Maximum resolution *	1920 x 1080 pixels	<b>Operational conditions</b>	
DDC/DDC2 supported	✓	Operating temperature (T-T)	0 - 40 °C
DDC2B support	✓	Storage temperature (T-T)	-20 - 60 °C
<b>Design</b>		Operating relative humidity (H-H)	0 - 80%
Rack mounting *	✓	<b>Weight &amp; dimensions</b>	
Rack capacity	1U	Width	589.2 mm
Product colour *	Black	Depth	480 mm
Housing material	Metal	Height	44 mm
LED indicators	✓	Weight	11.4 kg
Keyboard language	UK English	<b>Packaging content</b>	
<b>Display</b>		Manual	✓
Built-in display *	✓	<b>Logistics data</b>	
Display	LCD	Harmonized System (HS) code	85176200
Display diagonal	43.9 cm (17.3")		
Power			
Input voltage	100 - 240 V		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date