

GUC211V Portable Laptop Console Crash Cart Adapter (TAA Compliant)

- Diagnose and troubleshoot computers quickly from your laptop
- Perfect for: Data centers, IT departments, refurbishing centers or kiosk services
- Plug-N-Play No software needed
- Programmable hotkeys and macros
- Best value for reducing labor and hardware costs

USB Console to Laptop Crash Cart Adapter

IOGEAR's Portable Laptop Console Crash Cart Adapter provides instant computer access through your laptop. Simply connect the crash cart adapter to your target computer, kiosk, or server from your laptop, run the executable file, and you are good to go! Save time by programming hotkeys and macros for common tasks and avoid the hassle of lugging around unneeded equipment. This one-to-one solution is the perfect accessory for any IT professional.

- · Provides direct Laptop-to-Computer desktop access
- Programmable macros and hotkeys
- Plug-N-Play No additional software needed
- Bi-directional file transfer between connected laptop and computer
- Access laptop applications in virtual window without switching windows
- VGA resolutions up to 1920x1200 @60Hz
- Supports DisplayPort, HDMI, and DVI interface with IOGEAR's display adapters
- · BIOS level access
- Perform OS patching, software installation and diagnostic testing on remote computer

- Video recording and capture of remote computer*
- Mouse DynaSync[™] automatically synchronizes the laptop and connected computer's mouse movements
- On-screen virtual keyboard with multi-language support
- Supports Windows® 2000, Window Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10, Windows® 10.1
- · Adjust remote computer virtual window resolution
- Hot-Pluggable
- · Firmware upgradable

*Requires Java application v1.7.0_75 or later ready from laptop for video recording playback







• 1 x GUC211V

Adapter

• 1 x QSG

Portable Laptop

• 1 x USB Type A to

USB Mini-B Cable

Console Crash Cart

Package Contents



Requirements

• Laptop: Hardware: USB 2.0 Port Operating Systems: Windo ws® 2000, Windo ws® Vista, Windo ws® 7, Windo ws® 8.1, W indow s® 10 • Target Computer: Hardware: USB Туре A Port VGA Port Displa yPort Port (with a dapter) HDMI Port (with a dapter) DVI Port (with a dapter

Note:

The GUC211V only controls the connected computer through a direct cable connection. The GUC211V supports one-to-one direct KVM console; it cannot be used to control two standalone PCs, as it only provides one computer with desktop access User must know login credential of the connected computer if needed for access

)

www.iogear.com



Specifications

Function	GUC211V	Dimensions	GUC211V
Computer Connections		Unit Dimensions	
Direct	1	Height	2.375" (6.03cm)
CPU Connectors		Depth	0.75" (1.91cm)
Monitor	1 x VGA Male (Blue)	Length	2.18" (5.56cm); Mini to Type A USB Cable: 72" (183cm); USB and VGA Cables: 19"
Keyboard & Mouse	1 x USB Type A Male (Black)		(48.26cm)
Console Connectors		Unit Package Dimensions	
Keyboard, Mouse, and Monitor	1 x Mini-USB Female (Black)	Width	4.68" (11.9cm)
Video Resolution	1920x1200 @60Hz	Height	6.29" (16cm)
LEDs		Depth	2.3" (5.9cm)
On Line	1 x Blue	Master Carton	
Environment		Width	14.7" (37.5cm)
Operation Temperature	0~40C	Height	7" (17.8cm)
Storage Temperature	-20~60C	Depth	10" (25.4cm)
Humidity	0~80% RH, Non-condensing	Master Carton Qty.	12
Housing		Weight	
Case	Plastic	Master Carton Wt.	8.15lb (3.7kg)
Warranty	3 Years	Unit Pack Wt.	0.39lb (0.18kg)
		Unit Wt.	0.4lb (0.18kg)