ATEN

ATEN KL1108VN KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: KL1108VN-AXA-2XK06SG

Tuotteen nimi: KL1108VN

ATEN KL1108VN. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DVI-D/VGA. Kaapelitekniikka: 10/100/1000Base-T(X). Enimmäiserottelutarkkuus: 1920×1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19")





| Ports & interfaces | | Design | |
|---|------------------------------------|---|--|
| Number of computers controlled * 8 Keyboard port type * USB Mouse port type * USB Video port type * DVI-D/VGA DVI-D ports quantity 1 VGA (D-Sub) ports quantity 1 Console ports * DVI-D, USB A, VGA (D-Sub) | USB | Keyboard language | Spanish |
| | | Display | |
| | DVI-D/VGA 1 | Built-in display * Display Display diagonal On Screen Display (OSD) | LCD 48.3 cm (19") |
| Console USB ports quantity | 2 | Power | |
| Network Ethernet LAN | / | Input voltage AC input frequency | 100-240 V 50 - 60 Hz |
| Ethernet LAN (RJ-45) ports | 10 | Sustainability | |
| Cabling technology | 10/100/1000Base-T(X) | Compliance certificates | RoHS |
| Performance | | Operational conditions | |
| Maximum resolution * Scan interval DDC2B support | 1920 x 1200 pixels 1,255 s ✓ | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C -20 - 60 °C 0 - 80% |
| Design | | Weight & dimensions | |
| Rack mounting * Rack capacity Product colour * Housing material LED indicators | 1U Black Metal | Width Depth Height Weight Packaging content | 702.1 mm 480 mm 44 mm 15.2 kg |
| Push button | · / | Cables included | AC |
| | | Manual | ✓ |

