## ATEN KA7174 KVM-kytkin musta

Tuotemerkki : ATEN

Tuotekoodi: KA7174-AX-G




ATEN KA7174. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Konsoliportit: SPHD. HDtyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Kotelon materiaali: Metalli. Tulojännite: 5 V, Virrankulutus: 1,75 W. Tuotteen leveys: 86,4 mm, Tuotteen syvyys: 203 mm, Tuotteen korkeus: 25 mm





Ports & interfaces		Weight & dimensions	
Keyboard port type * Mouse port type * Console ports * Serial port type	USB, PS/2 USB, PS/2 SPHD DE-9 (DB-9)	Width Depth Height Weight	86.4 mm 203 mm 25 mm 490 g
Serial ports quantity	2	Packaging data	
DC-in jack	✓	Package width	62 mm
Network		Package depth	283 mm
Ethernet LAN Ethernet LAN (RJ-45) ports <b>Performance</b>	✓ 1	Package height Package volume Package weight	173 mm 3114.85 cm <sup>3</sup> 1.02 kg
HD type *	WUXGA	Package type	Box
Maximum resolution *	1920 x 1200 pixels	Packaging content	
Video bandwidth Design Rack mounting * Product colour *	60 Hz × Black	Packaging content	1x KA7174 KVM Adapter Module with USB, PS/2, and RS-232 Local Console 1x power adapter 1x KVM cable (VGA, USB, PS/2) 1x console cable (VGA, USB, PS/2) 1x foot pad set (4pcs) 1x user instructions
Housing material	Metal	Other Features           UD ports         1 x SPHD, 1 x 6-pin Mini-DIN, 1 x USB Type A           Compacibility         K02116VA.KN2132VA, RN4116VA.XN4142VA.XN4164V,2L-5301UP,XN8132VA	2L-5302UP,XNB164V,2L-5303UP,XN2124VA,XN2140VA,XN4124VA,XN4140VA,VE-RMK1U,XN1132V,2XRT-0015G,K47171A4
LED indicators	✓	Logistics data	
Push button	1	Harmonized System (HS) code	85176200
Display		Master (outer) case width	300 mm
Built-in display *	×	Master (outer) case length	336 mm
Power		Master (outer) case height	194 mm
Input voltage	5 V	Master (outer) case gross weight Master (outer) case volume	5.61 kg 19538.62 cm <sup>3</sup>
Power consumption (typical)	5 v 1.75 W	Products per master (outer) case	5 pc(s)
Operational conditions	1.75 1	Country of origin	Taiwan
Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 50 °C -20 - 60 °C 0 - 95% 0 - 95%		



4710469341595

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.