ATEN

ATEN KL1516AiM KVM switch Rack mounting Black

Brand : ATEN Product code: KL1516AIM-AXA-2XK06DNG

Product name: KL1516AiM

16-Port Dual Rail LCD KVM Switch LCD Console + Cat 5 High-Density KVM Switch with KVM over IP ATEN KL1516AiM. Keyboard port type: USB, PS/2, Mouse port type: USB, PS/2, Video port type: VGA. Maximum resolution: 1600 x 1200 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Keyboard language: Danish, Norwegian. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Power consumption (typical): 30 W





Number of computers controlled * 16 Built-in display * Keyboard port type * USB, PS/2 Display LCD Mouse port type * USB, PS/2 Display diagonal 43.2 cm (17") Video port type * VGA On Screen Display (OSD) VGA (D-Sub) ports quantity 1 Console ports * PS/2, USB A, VGA (D-Sub) Console USB ports quantity 2 Input voltage 100-240 V USB connector type USB Type-A AC input frequency 50 - 60 Hz					
Keyboard port type* USB, PS/2 Display diagonal 43.2 cm (17*) Mouse port type* VGA On Screen Display (OSD) Image: Composition of Com	Ports & interfaces		Display		
Console ports * PS/2, USB A, VGA (D-Sub) Power Console USB ports quantity 2 Input voltage 100-240 V USB connector type USB Type-A AC input frequency 50 - 60 Hz Network Power consumption (typical) 30 W System requirements Ethernet LAN System requirements Performance Windows operating systems Maximum resolution * 1600 x 1200 pixels Sustainability Automatic switching Y Scan interval 1,255 s DDC2B support Y Daisy chain Y Design Operating temperature (T-T) 0 - 40 °C Storage temperature (T-T) - 20 - 60 °C Design Weight & dimensions Rack capacity Ill Width 701.2 mm Product colour * Black Depth 44 mm <td colspan<="" td=""><td rowspan="3">Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports * Console USB ports quantity</td><td rowspan="3">USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2</td><td>Display Display diagonal</td><td>LCD 43.2 cm (17")</td></td>	<td rowspan="3">Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports * Console USB ports quantity</td> <td rowspan="3">USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2</td> <td>Display Display diagonal</td> <td>LCD 43.2 cm (17")</td>	Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports * Console USB ports quantity	USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2	Display Display diagonal	LCD 43.2 cm (17")
Console USB ports quantity USB connector type USB Type-A Network Ethernet LAN Performance Maximum resolution * 1600 x 1200 pixels Act input frequency More and interval DDC2B support Daisy chain Rack mounting * Rack mounting * Rack capacity Rack capacity Rack capacity Product colour * Black	Power				
Network Ethernet LAN Y Windows operating systems supported Y Performance 1600 x 1200 pixels Sustainability X Automatic switching Y Compliance certificates RoHS Scan interval 1,255 s Operational conditions Y DDC2B support Y Operating temperature (T-T) -20 - 60 °C Design Y Storage temperature (T-T) -20 - 60 °C Design Y Weight & dimensions Rack mounting * Y Weight & dimensions Rack capacity 1U Woldth 701.2 mm Product colour * Black Depth 480 mm LED indicators Y Height 44 mm Keyboard language Danish, Norwegian Weight 15.2 kg	AC input frequency			50 - 60 Hz	
Performance Maximum resolution * 1600 x 1200 pixels Automatic switching Automatic switching Compliance certificates DDC2B support Daisy chain Pesign Rack mounting * Ack capacity Product colour * Black Danish, Norwegian Danish, Norwegian Windows operating systems supported Sustainability Compliance certificates RoHS RoHS Poperational conditions Operating temperature (T-T) Operating temperature (T-T) Operating relative humidity (H-H) Operating relative humidity (H-H) Width To1.2 mm Voluth	Network		1 131 /	30 W	
Performance supported Yes Maximum resolution * 1600 x 1200 pixels Sustainability Automatic switching ✓ Compliance certificates RoHS Scan interval 1,255 s Operational conditions DDC2B support ✓ Operating temperature (T-T) 0 - 40 °C Storage temperature (T-T) -20 - 60 °C Compliance Pesign ✓ Operating temperature (T-T) 0 - 80% Veight & dimensions Veight & dimensions Rack capacity 1U Width 701.2 mm Product colour * Black Depth 480 mm LED indicators ✓ Height 44 mm Keyboard language Danish, Norwegian Weight 15.2 kg Packaging content	Ethernet LAN	✓			
Automatic switching Scan interval DDC2B support Daisy chain Design RoHS Operational conditions Operating temperature (T-T) Storage temperature (T-T) O - 40 °C Storage temperature (T-T) O - 80% Pack mounting * Rack mounting * Rack capacity Product colour * LED indicators Keyboard language Danish, Norwegian Operating temperature (T-T) O - 40 °C Storage temperature (T-T) O - 80% Weight & dimensions Width 701.2 mm 701.2 mm 480 mm Height Height Weight & dimensions Weight Height	Performance		. 9 ,	✓	
Scan interval DDC2B support Daisy chain Pesign ROHS Operational conditions Operating temperature (T-T) Operating relative humidity (H-H) Operating temperature (T-T) Operating temperatu		·	Sustainability		
DDC2B support Daisy chain Pesign Rack mounting * Rack capacity Product colour * LED indicators Keyboard language DDC2B support V Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating temperature (T-T) Operating temperature	Scan interval	1,255 s	Compliance certificates	RoHS	
Daisy chain Daisy chain Pesign Operating temperature (T-T) Storage temperature (T-T) O - 40 °C Storage temperature (T-T) O - 80 °C Operating relative humidity (H-H) O - 80% Weight & dimensions Width Tol.2 mm Product colour * Black Depth Height Keyboard language Danish, Norwegian Packaging content Packaging content			Operational conditions		
Rack mounting *		•	1 3 1 , ,		
Rack capacity Product colour * Black Depth Height 480 mm Height Keyboard language Danish, Norwegian Weight Packaging content Police tames 101.2 mm Height 440 mm Height 15.2 kg Packaging content	Design		Operating relative humidity (H-H)	0 - 80%	
Product colour * Black Depth 480 mm LED indicators ✓ Height 44 mm Keyboard language Danish, Norwegian Weight 15.2 kg Packaging content	Rack mounting *	1U Black ✓	Weight & dimensions		
	Product colour * LED indicators		Depth Height	480 mm 44 mm	
Manual ✓			Packaging content		
			Manual	1	

