

## ATEN KL1508AM KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: KL1508AM-AXA-2XK06DNG

Tuotteen nimi: KL1508AM

ATEN KL1508AM. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Enimmäiserottelutarkkuus: 1600 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 10, Näppäimistön kieli: Tanska, Norjalainen. Näyttö: LCD, Näytön halkaisija: 43,2 cm (17").

Tulojännite: 100-240 V, AC-syöttötaajuus: 50 - 60 Hz, Virrankulutus: 24,4 W





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports * Console USB ports quantity USB connector type	8 USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2 USB Type-A	Display Display diagonal On Screen Display (OSD)	LCD 43.2 cm (17") ✓
		Power	
		Input voltage AC input frequency Power consumption (typical)	100-240 V 50 - 60 Hz 24.4 W
Performance		System requirements	
Maximum resolution *	1600 x 1200 pixels	Windows operating systems supported	<b>✓</b>
Automatic switching Scan interval	1.255 s	Operational conditions	
Design	-,	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Rack mounting *	✓	Operating relative humidity (H-H)	0 - 80%
Rack capacity	1U Black ✓ Danish, Norwegian	Weight & dimensions	
Product colour * LED indicators Keyboard language Display		Width Depth Height Weight	701.2 mm 480 mm 44 mm 15.2 kg
Built-in display *	•	Packaging content	
		Manual	✓

