



ATEN KL1516AiN KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: KL1516AIN-AXA-2XK06A1G

Tuotteen nimi : KL1516AiN

ATEN KL1516AiN. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Enimmäiserottelutarkkuus: 1600 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Näppäimistön kieli: Englanti (US). Näyttö: LCD, Näytön halkaisija: 48,3 cm (19"). Tulojännite: 100-240 V, AC-syöttötaajuus: 50 - 60 Hz, Virrankulutus: 27,5 W



Ports & interfaces

| | |
|----------------------------------|--------------------------|
| Number of computers controlled * | 16 |
| Keyboard port type * | USB, PS/2 |
| Mouse port type * | USB, PS/2 |
| Video port type * | VGA |
| VGA (D-Sub) ports quantity | 1 |
| Console ports * | PS/2, USB A, VGA (D-Sub) |
| Console USB ports quantity | 2 |
| USB connector type | USB Type-A |

Network

| | |
|--------------|---|
| Ethernet LAN | ✓ |
|--------------|---|

Performance

| | |
|----------------------|--------------------|
| Maximum resolution * | 1600 x 1200 pixels |
| Automatic switching | ✓ |
| Scan interval | 1,255 s |
| DDC2B support | ✓ |
| Daisy chain | ✓ |

Design

| | |
|-------------------|------------|
| Rack mounting * | ✓ |
| Rack capacity | 1U |
| Product colour * | Black |
| LED indicators | ✓ |
| Keyboard language | US English |

Display

| | |
|-------------------------|---------------|
| Built-in display * | ✓ |
| Display | LCD |
| Display diagonal | 48.3 cm (19") |
| On Screen Display (OSD) | ✓ |

Power

| | |
|-----------------------------|------------|
| Input voltage | 100-240 V |
| AC input frequency | 50 - 60 Hz |
| Power consumption (typical) | 27.5 W |

System requirements

| | |
|-------------------------------------|---|
| Windows operating systems supported | ✓ |
|-------------------------------------|---|

Sustainability

| | |
|-------------------------|------|
| Compliance certificates | RoHS |
|-------------------------|------|

Operational conditions

| | |
|-----------------------------------|-------------|
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -20 - 60 °C |
| Operating relative humidity (H-H) | 0 - 80% |

Weight & dimensions

| | |
|--------|----------|
| Width | 701.2 mm |
| Depth | 480 mm |
| Height | 44 mm |
| Weight | 15.4 kg |

Packaging content

| | |
|--------|---|
| Manual | ✓ |
|--------|---|

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date