ATEN

ATEN KL1508AiN KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: KL1508AIN-AXA-2XK06FG

Tuotteen nimi: KL1508AiN

ATEN KL1508AiN. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Enimmäiserottelutarkkuus: 1600 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19"). Tulojännite: 100-240 V, ACsyöttötaajuus: 50 - 60 Hz, Virrankulutus: 27,5 W





| Ports & interfaces | | Display | |
|---|---|---|--|
| Number of computers controlled * Keyboard port type * Mouse port type * Video port type * | 8 USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2 USB Type-A | Display Display diagonal On Screen Display (OSD) | LCD 48.3 cm (19") ✓ |
| | | Power | |
| VGA (D-Sub) ports quantity Console ports * Console USB ports quantity USB connector type | | Input voltage AC input frequency Power consumption (typical) | 100-240 V 50 - 60 Hz 27.5 W |
| Network | N | System requirements | |
| Ethernet LAN | ✓ | Windows operating systems supported | 1 |
| Performance | | Sustainability | |
| Maximum resolution * | 1600 x 1200 pixels | Compliance certificates | RoHS |
| Automatic switching | / | Operational conditions | |
| Scan interval DDC2B support Daisy chain | 1,255 s ✓ | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C -20 - 60 °C 0 - 80% |
| Design | | Weight & dimensions | |
| Rack mounting * Rack capacity Product colour * LED indicators | √ 1U Black ✓ | Width Depth Height Weight | 701.2 mm 480 mm 44 mm 15.4 kg |
| Display | | Packaging content | |
| Built-in display * | ✓ | Manual | ✓ |

