## **ATEN**

## ATEN KL1516AiM KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: KL1516AIM-AXA-2XK06UG

Tuotteen nimi: KL1516AiM

ATEN KL1516AiM. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Enimmäiserottelutarkkuus: 1600 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Näppäimistön kieli: Englanti (UK). Näyttö: LCD, Näytön halkaisija: 43,2 cm (17"). Tulojännite: 100-240 V, AC-syöttötaajuus: 50 - 60 Hz, Virrankulutus: 30 W





| Ports & interfaces   |  | Display   |  |
|--|--|---|--|
| Number of computers controlled * Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports * Console USB ports quantity USB connector type | 16 USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2 USB Type-A | Built-in display * Display Display diagonal On Screen Display (OSD)   | ✓<br>LCD<br>43.2 cm (17")<br>✓         |
|  |  | Power Input voltage AC input frequency  | 100-240 V<br>50 - 60 Hz                |
| Network  |  | Power consumption (typical)   | 30 W                                   |
| Ethernet LAN   | ✓  | System requirements   |  |
| Performance  |  | Windows operating systems supported   | ✓                                      |
| Maximum resolution * 1600 x 1200 pix Automatic switching  Scan interval 1,255 s  DDC2B support  Daisy chain  Design  |  | <b>Sustainability</b> Compliance certificates   | RoHS                                   |
|  | •  | Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H) | 0 - 40 °C<br>-20 - 60 °C<br>0 - 80%    |
| Rack mounting * Rack capacity Product colour * LED indicators Keyboard language  | ✓<br>1U<br>Black<br>✓<br>UK English                                | Weight & dimensions Width Depth Height Weight Packaging content   | 701.2 mm<br>480 mm<br>44 mm<br>15.2 kg |
|  |  | Manual  | <b>✓</b>                               |

