



## ATEN KL1516AiM KVM switch Rack mounting Black

**Brand :** ATEN

**Product code:** KL1516AIM-AXA-2XK06GG

**Product name :** KL1516AiM

16-Port Dual Rail LCD KVM Switch LCD Console + Cat 5 High-Density KVM Switch with KVM over IP ATEN KL1516AiM. Keyboard port type: USB, PS/2, Mouse port type: USB, PS/2, Video port type: VGA. Maximum resolution: 1600 x 1200 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Keyboard language: German. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Power consumption (typical): 30 W



|                                  |                          |                                     |               |
|----------------------------------|--------------------------|-------------------------------------|---------------|
| <b>Ports &amp; interfaces</b>    |                          | <b>Display</b>                      |               |
| Number of computers controlled * | 16                       | Built-in display *                  | ✓             |
| Keyboard port type *             | USB, PS/2                | Display                             | LCD           |
| Mouse port type *                | USB, PS/2                | Display diagonal                    | 43.2 cm (17") |
| Video port type *                | VGA                      | On Screen Display (OSD)             | ✓             |
| VGA (D-Sub) ports quantity       | 1                        | <b>Power</b>                        |               |
| Console ports *                  | PS/2, USB A, VGA (D-Sub) | Input voltage                       | 100-240 V     |
| Console USB ports quantity       | 2                        | AC input frequency                  | 50 - 60 Hz    |
| USB connector type               | USB Type-A               | Power consumption (typical)         | 30 W          |
| <b>Network</b>                   |                          | <b>System requirements</b>          |               |
| Ethernet LAN                     | ✓                        | Windows operating systems supported | ✓             |
| <b>Performance</b>               |                          | <b>Sustainability</b>               |               |
| Maximum resolution *             | 1600 x 1200 pixels       | Compliance certificates             | RoHS          |
| Automatic switching              | ✓                        | <b>Operational conditions</b>       |               |
| Scan interval                    | 1,255 s                  | Operating temperature (T-T)         | 0 - 40 °C     |
| DDC2B support                    | ✓                        | Storage temperature (T-T)           | -20 - 60 °C   |
| Daisy chain                      | ✓                        | Operating relative humidity (H-H)   | 0 - 80%       |
| <b>Design</b>                    |                          | <b>Weight &amp; dimensions</b>      |               |
| Rack mounting *                  | ✓                        | Width                               | 701.2 mm      |
| Rack capacity                    | 1U                       | Depth                               | 480 mm        |
| Product colour *                 | Black                    | Height                              | 44 mm         |
| LED indicators                   | ✓                        | Weight                              | 15.2 kg       |
| Keyboard language                | German                   | <b>Packaging content</b>            |               |
|                                  |                          | Manual                              | ✓             |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-NOV-2024. Prints or copies of Information are only valid on the printed Publication date