## **ATEN**

## ATEN KL1508AIM KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: KL1508AIM-DE

Tuotteen nimi: KL1508AIM

ATEN KL1508AIM. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Näyttö: LCD, Näytön halkaisija: 43,2 cm (17"). Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz





Danta C intenferes		Diamlay	
Ports & interfaces		Display	
Mouse port type * USB, PS/2 Video port type * VGA VGA (D-Sub) ports quantity 1	USB, PS/2 USB, PS/2	Display diagonal	43.2 cm (17")
		On Screen Display (OSD)	✓
		Power	
	1 PS/2, USB A, VGA (D-Sub) 2	Power source Input voltage AC input frequency Input current Power consumption (typical)	AC 100 - 240 V 50 - 60 Hz 1 A 22.2 W
Network			ZZ.Z W
Ethernet LAN Ethernet LAN (RJ-45) ports	<b>✓</b> 10	System requirements Windows operating systems supported	·
Performance		Linux operating systems supported	✓
HD type * Maximum resolution * Video bandwidth Scan interval	WUXGA 1920 x 1200 pixels 60 Hz 1,255 s	Mac operating systems supported	<b>✓</b>
		Sustainability	
		Compliance certificates	RoHS
Daisy chain	·	Operational conditions	
Firmware upgradeable	✓	Operating temperature (T-T)	0 - 40 °C
Design		Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 60 °C 0 - 80%
Rack mounting *	capacity 1U uct colour * Black ing material Metal ndicators	Weight & dimensions	
Rack capacity Product colour * Housing material LED indicators Push button		Width Depth Height Weight	480 mm 701.2 mm 44 mm 15.2 kg
Hot keys	<b>v</b>	Packaging content	
Keyboard language	German	Cables included	AC, KVM
Display		Manual	✓
Built-in display *	<b>/</b>	Rack mount kit	✓
Display	LCD		

