ATEN

ATEN KL1516AiM KVM switch Rack mounting Black

Brand: ATEN Product code: KL1516AIM-AXA-2XK06SG

Product name: KL1516AiM

16-Port Dual Rail LCD KVM Switch LCD Console + Cat 5 High-Density KVM Switch with KVM over IP ATEN KL1516AiM. Keyboard port type: USB, PS/2, Mouse port type: USB, PS/2, Video port type: VGA. Maximum resolution: 1600 x 1200 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Keyboard language: Spanish. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Power consumption (typical): 30 W





Ports & interfaces Display Number of computers controlled* 16 Built-in display* ✓ Keyboard port type * USB, PS/2 Display LCD Mouse port type * USB, PS/2 Display diagonal 43.2 cm (17*) Video port type * VGA On Screen Display (OSD) ✓ VGA (D-Sub) ports quantity 1 Power Console USB ports quantity 2 Input voltage 100-240 V Console USB ports quantity 2 AC input frequency 50 - 60 Hz USB connector type USB Type-A AC input frequency 50 - 60 Hz VBW consummers and type an				
Keyboard port type *USB, PS/2Display diagonalLCDMouse port type *USB, PS/2Display diagonal43.2 cm (17")Video port type *VGAOn Screen Display (OSD)*VGA (D-Sub) ports quantity1PowerConsole ports *PS/2, USB A, VGA (D-Sub)Input voltage100-240 VConsole USB ports quantity2Input voltage100-240 VUSB connector typeUSB Type-AAC input frequency50 - 60 HzNetworkSystem requirementsEthernet LAN*System requirementsPerformanceWindows operating systems supported*Maximum resolution *1600 x 1200 pixelsSustainabilityAutomatic switching*Compliance certificatesRoHSScan interval1,255 sOperating certificatesRoHSDDC2B support*Operating temperature (T-T)0 - 40 °CDaisy chain*Operating relative humidity (H-H)0 - 80%Pack mounting **Weight & dimensionsRack capacity1UWidth701.2 mmProduct colour *BlackDepth480 mmLED indicators*Height44 mmKeyboard languageSpanishWeight Capacity15.2 kg	Ports & interfaces		Display	
Console ports*PS/2, USB A, VGA (D-Sub)PowerConsole USB ports quantity2Input voltage100-240 VUSB connector typeUSB Type-AAC input frequency50 - 60 HzNetworkSystem requirementsEthernet LANSystem requirementsPerformanceSystem requirementsMaximum resolution *1600 x 1200 pixelsSustainabilityAutomatic switchingYCompliance certificatesRoHSScan interval1,255 sOperating temperature (T-T)0 - 40 °CDaisy chainYOperating temperature (T-T)0 - 40 °CDaisy chainYDesignOperating relative humidity (H-H)0 - 80%Rack capacityIUWidth701.2 mmProduct colour*BlackDepth480 mmLED indicatorsYKeyboard languageSpanishWeight & dimensionsKeyboard languageSpanishWeight & dimensionsLED indicatorsY	Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports * Console USB ports quantity	USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2	Display Display diagonal	LCD 43.2 cm (17")
USB connector type USB Type-A AC input frequency Power consumption (typical) 30 W Network Ethernet LAN Performance Maximum resolution * Automatic switching Can interval DDC2B support Daisy chain Pesign Acc input frequency System requirements Windows operating systems supported Compliance certificates Compliance certificates Perational conditions Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating relative humidity (H-H) Operating relative humidity (H-H) Operating temperature Weight & dimensions Rack capacity IU Width Product colour * Black Depth Height Meight Meigh			Power	
Network Ethernet LAN Y Windows operating systems supported Y Performance \$\text{Mindows operating systems supported}\$ Y Maximum resolution * \$1600 x 1200 pixels \$\text{Sustainability}\$ Automatic switching \$\text{Compliance certificates}\$ \$\text{RoHS}\$ Scan interval \$1,255 s \$\text{Operating temperature (T-T)}\$ \$0 - 40 °C DDC2B support \$\text{Y}\$ \$\text{Operating temperature (T-T)}\$ \$-20 - 60 °C \$\text{Design}\$ \$\text{Y}\$ \$\text{Meight & dimensions}\$ \$\text{Rack mounting *}\$ \$\text{Y}\$ \$\text{Weight & dimensions}\$ \$\text{Rack capacity}\$ \$10 \$\text{Windows operating systems supported \$\text{701.2 mm}\$ \$\text{Product colour *}\$ \$\text{Black}\$ \$\text{Depth}\$ \$480 mm \$\text{LED indicators}\$ \$\text{Y}\$ \$\text{Perchasing temperature (T-T)}\$ \$\text{701.2 mm}\$ \$\text{Resplance operating temperature (T-T)}\$ \$\text{701.2 mm}\$ \$\text{Perchasing temperature (T-T)}\$ \$\text{701.2 mm}\$ \$\text{Rack capacity}\$ \$\text{Black}\$ \$\text{Depth}\$ \$\text{44 mm}\$ \$\text{LED indicators}\$ \$\text{Y}\$ \$			AC input frequency	50 - 60 Hz
Performance Maximum resolution * 1600 x 1200 pixels Automatic switching Scan interval Disay chain Design Rack mounting * Ack capacity Rack capacity Product colour * Black LED indicators Keyboard language Windows operating systems supported Sustainability Compliance certificates RoHS Poperational conditions Operating temperature (T-T) 0 - 40 °C Storage temperature (T-T) -20 - 60 °C Operating relative humidity (H-H) 0 - 80% Weight & dimensions Weight & dimensions 480 mm 480 mm 440 mm Weight Weight Weight Weight Weight Weight Weight Weight Weight Packaging content	Network		1 131 7	30 W
PerformancesupportedMaximum resolution *1600 x 1200 pixelsSustainabilityAutomatic switching✓Compliance certificatesRoHSScan interval1,255 sOperational conditionsDDC2B support✓Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)0 - 40 °C - 20 - 60 °CDesign✓Weight & dimensionsRack mounting *✓Weight & dimensionsRack capacity1UWidth701.2 mmProduct colour *BlackDepth480 mmLED indicators✓Height44 mmKeyboard languageSpanishWeight15.2 kgPackaging content	Ethernet LAN	✓		
Automatic switching Scan interval DDC2B support Daisy chain Rack mounting * Rack capacity Product colour * Black LED indicators Keyboard language Automatic switching I,255 s Compliance certificates RoHS Operational conditions Operating temperature (T-T) 0 - 40 °C Storage temperature (T-T) -20 - 60 °C Operating relative humidity (H-H) 0 - 80% Weight & dimensions Width 701.2 mm Height 480 mm Height 44 mm Neight Administration Weight Depth 15.2 kg	Performance		. 9 ,	✓
Scan interval DDC2B support Daisy chain Pesign Roh Roh Policy temperature (T-T) Operating temperature (T-T) Operating relative humidity (H-H) Operating temperature (T-T) Operating temp		·	Sustainability	
DDC2B support Daisy chain Pesign Rack mounting * Rack capacity Product colour * LED indicators Keyboard language Poperating temperature (T-T) O - 40 °C Storage temperature (T-T) Operating relative humidity (H-H) O - 80% Weight & dimensions Width 701.2 mm 701.2 mm 480 mm Height Height Weight Weight Weight Height Height Height Height Packaging content	Scan interval	1,255 s	Compliance certificates	RoHS
Daisy chain Daisy chain Pesign Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating temperature (T-T) Operating temperature (Operational conditions	
Rack mounting * Rack capacity Product colour * LED indicators Keyboard language Weight & dimensions Width Found to the product to lour * Width Found to pepth Found to pe		•		
Rack capacity Product colour * LED indicators Keyboard language 10 Width 701.2 mm 480 mm Height 44 mm Weight 15.2 kg Packaging content	Design		Operating relative humidity (H-H)	0 - 80%
Product colour * Black Depth 480 mm LED indicators ✓ Height 44 mm Keyboard language Spanish Weight 15.2 kg Packaging content	Rack mounting *	✓	Weight & dimensions	
	Product colour * LED indicators	Black ✓	Depth Height	480 mm 44 mm
Manual			Packaging content	
Harradi •			Manual	✓

