## **ATEN**

## ATEN KL1516AN KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: KL1516AN-DE

Tuotteen nimi: KL1516AN

ATEN KL1516AN. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19"). Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports *	512 USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub)	Display diagonal	48.3 cm (19")
		On Screen Display (OSD)	✓
		Power	
		Power source	AC
		Input voltage	100 - 240 V
Console USB ports quantity	2	AC input frequency	50 - 60 Hz
PS/2 ports quantity	2	Input current	1 A
Network		Power consumption (typical)	22.1 W
Ethernet LAN	1	System requirements	
Ethernet LAN (RJ-45) ports	16	Windows operating systems supported	✓
Performance		Linux operating systems supported	✓
HD type * Maximum resolution * Video bandwidth	WUXGA 1920 x 1200 pixels 60 Hz	Mac operating systems supported	<b>✓</b>
		Sustainability	
Scan interval	1,255 s	Compliance certificates	RoHS
Daisy chain	✓	Operational conditions	
Firmware upgradeable	<b>✓</b>	Operating temperature (T-T)	0 - 40 °C
Design		Storage temperature (T-T)	-20 - 60 °C
	,	Operating relative humidity (H-H)	0 - 80%
Rack mounting * Rack capacity	<b>√</b> 1U	Weight & dimensions	
Product colour *	Black	Width	480 mm
Housing material	Metal	Depth	701.2 mm
LED indicators	1	Height	44 mm
Push button	<b>√</b>	Weight	15.4 kg
Hot keys	<b>✓</b>	Packaging content	
Keyboard language	German	Cables included	AC, KVM
Display		Manual	✓
Built-in display *	<b>✓</b>	Rack mount kit	✓
Display	LCD		
Display	LCD		

