



ATEN SN3401P päätepalvelin RS-232/422/485

Tuotemerkki : ATEN

Tuotekoodi: SN3401P-AX

Tuotteen nimi : SN3401P

ATEN SN3401P. Virtalähteen malli: DC, PoE, Tehonkulutus (maks.): 1,3 W, Virrankulutus: 1,18 W. LED-merkkivalot: Teho, Tila. Tuotteen leveys: 117 mm, Tuotteen syvyys: 98 mm, Tuotteen korkeus: 26 mm. Tuotteen väri: musta, Kotelon materiaali: Metalli, Turvallisuus: UL 60950-1, UL 62368-1. Jalkatyynyjen lukumäärä: 4 kpl



Technical details		Weight & dimensions	
Serial ports quantity *	1	Weight	210 g
Serial interface type	RS-232/422/485	Package width	59 mm
Isolation	1.5 kV	Package depth	239 mm
Surge protection voltage	2 kV	Package height	160 mm
Ethernet LAN data rates	10,100 Mbit/s	Package weight	420 g
Electrostatic Discharge (ESD) protection	8 kV	Operational conditions	
Data transfer rate	100 Mbit/s	Operating temperature (T-T)	0 - 60 °C
Networking standards	IEEE 802.3af	Storage temperature (T-T)	-40 - 75 °C
Flow control support	✓	Operating relative humidity (H-H)	5 - 95%
Baud rate	921.6 Kbit/s	Design	
RS-232 signals	CTS, DCD, DSR, DTR, GND, RTS, RXD, TXD	Product colour	Black
RS-422 signals	GND, RxD+, RxD-, TxD+, TxD-	Housing material	Metal
RS-485 signals	Data+, Data-, GND, RxD+, RxD-, TxD+, TxD-	Reset button	✓
Data bits	5, 6, 7, 8	DIN rail mounting	✓
Flow Control type	DTR/DSR, RTS/CTS, XON/XOFF	Safety	UL 60950-1, UL 62368-1
Parity bit	Even, Mark, No, Odd, Space	Packaging content	
Stop bits	1, 1.5, 2	DIN rail kit included	✓
Compliance certificates	RoHS	Terminal block included	✓
Ports & interfaces		Number of foot pads	4 pc(s)
Ethernet LAN	✓	User guide	✓
Ethernet LAN (RJ-45) ports	1	Logistics data	
Terminal block port	✓	Country of origin	Taiwan
Power		Products per master (outer) case	10 pc(s)
Power source type	DC, PoE	Master (outer) case gross weight	5.51 kg
Power consumption (max)	1.3 W	Package volume	2265.35 cm ³
Power consumption (typical)	1.18 W	Master (outer) case volume	27467.33 cm ³
Input voltage	100 - 240 V	Master (outer) case length	490 mm
Input frequency	50 - 60 Hz	Master (outer) case width	315 mm
Output voltage	9 - 48 V	Master (outer) case height	178 mm
Indication		Master (outer) case net weight	3.3 kg
LED indicators	Power, Status	Sustainability	
		Sustainability compliance	✓

Weight & dimensions

Width	117 mm
Depth	98 mm
Height	26 mm

Sustainability

Sustainability certificates	UL ECOLOGO
-----------------------------	------------



4710469341564

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date