

APC Easy 3S UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 30 kVA 30000 W

Tuotemerkki : APC Tuotekoodi: E3SUPS30KHB

Tuotteen nimi: Easy 3S


APC Easy 3S. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 30 kVA, Lähtöteho: 30000 W. Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 240 V. Kotelo: Tower, Tuotteen väri: Valkoinen, Jäähdytyksen tyyppi: Aktiivinen. Tuotteen leveys: 500 mm, Tuotteen syvyys: 969 mm, Tuotteen korkeus: 1400 mm





Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Tower
Output power capacity *	30 kVA	Cooling type	Active
Output power *	30000 W	Product colour *	White
Input operation voltage (min) *	304 V	LED indicators	✓
Input operation voltage (max) $*$	477 V	International Protection (IP) code	IP20
Input frequency *	45/65 Hz		CE, EAC, IEC 62040-1-1, IEC
Output operation voltage (min)	380 V	Certification	62040-2, IEC 62040-3, IEC 62040-4,
Output operation voltage (max)	415 V		ISTA 2B, RCM, WEEE REACH
Output frequency	50/60 Hz	Operational conditions	
Maximum current	55 A	Operating temperature (T-T)	0 - 40 °C
Number of input phases	3	Storage temperature (T-T)	-15 - 40 °C
Number of output phases	3	Operating relative humidity (H-H)	0 - 95%
Three-phase output voltage supported	400 V	Storage relative humidity (H-H) Operating altitude	0 - 95% 0 - 999.9 m
Efficiency	95%	Non-operating altitude	0 - 15000 m
Input power factor	0.99	, ,	0 13000 m
ECO mode	✓	Technical details	
Emergency Power Off (EPO)	✓	Compliance certificates	RoHS
Output voltage Total Harmonic Distortion (THD)	3%	Weight & dimensions	500
Input current Total Harmonic Distortion (THD)	3%	Width Depth	500 mm 969 mm
Noise level	63 dB	Height	1400 mm
Battery		Weight Pattory width	152 kg 68.3 cm
Battery technology	Sealed Lead Acid (VRLA)	Battery width	68.3 cm 111.4 cm
battery technology	Scaled Lead Acid (VILA)	Battery depth	111.4 CIII

Battery		Weight & dimensions	
Battery voltage	240 V	Battery height	164 cm
		Battery weight	190 kg
		Logistics data	
		Harmonized System (HS) code	85078000





731304340812

0731304340812

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.