

Product datasheet

Specifications



APC Smart-UPS Ultra, 2200VA 230V 1U, with Lithium-Ion Battery, with Network Management Card Embedded

SRTL2K2RM1UINC

Overview

Lead time Usually in Stock

Main

Main Input Voltage 230 V AC

Other Input Voltage 230 V

Main Output Voltage 230 V AC

Other Output Voltage 230 V

Rated power in W 2200 W

Rated power in VA 2200 VA

Input Connection Type BS1363A British

Output connection type 3 IEC 320 C13

Number of rack unit 1U

Number of cables 1

Battery type Li-Ion (Lithium-Ion)

Provided equipment RJ45 cable

Batteries & Runtime

Battery recharge time 1.5 h

Number of battery replacement quantity 1

Battery voltage 50 V

Battery charger power 448 W rated

Battery design life 8...10 year(s)

Battery power in VAh 336 VAh runtime

Battery option SRTL50RMBP1U-LI 1 1240 VAh

Extended runtime 1

Replacement battery [APCRBC173-LI](#) 

General

Product web sub-family High density

Redundant	No
-----------	----

Physical

Colour	Silver grey
Height	43 mm
Width	432 mm
Depth	560 mm
Net weight	15.9 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	1
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Network frequency	50/60 Hz auto-sensing
Input voltage limits	160...275 V adjustable 220...240 V AC

Output

Maximum configurable power in W	2200 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	On-Line
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	2200 VA

Conformance

Product certifications	CE
Marking	CE Mark
Standards	EN/IEC 62040-1

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dB
IP degree of protection	IP20

Communications & Management

Preinstalled device	Network management card with environmental monitoring
Control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.82 cm
Package 1 Width	56.4 cm
Package 1 Length	76.4 cm
Package 1 Weight	24.18 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	5 years repair or replace
----------	---------------------------

Recommended replacement(s)