



APC SRTL2K2RM1UINC UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2,2 kVA 2200 W 5 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRTL2K2RM1UINC

Tuotteen nimi : SRTL2K2RM1UINC



APC SRTL2K2RM1UINC. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 2200 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Tyyppi F, Ulostulojen määrä: 5 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion), Akun kapasiteetti: 336 VAh, Akun jännite: 50 V. Kotelo: Telineasennettava, Tuotteen väri: Harmaa, Telineen kapasiteetti: 1U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 560 mm, Tuotteen korkeus: 43 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery life (max)	10 year(s)
Output power capacity *	2.2 kVA	Battery recharge time	1.5 h
Output power *	2200 W	Design	
Waveform *	Sine	Form factor *	Rackmount
Input operation voltage (min) *	160 V	Rack capacity	1U
Input operation voltage (max) *	275 V	Product colour *	Grey
Input frequency *	50/60 Hz	Control type	Touch
Output operation voltage (max)	230 V	Display type	LCD
Output frequency	50/60 Hz	LED indicators	✓
Crest factor	3:1	International Protection (IP) code	IP20
Emergency Power Off (EPO)	✓	Operational conditions	
Noise level	55 dB	Operating temperature (T-T)	0 - 40 °C
Audible alarm(s)	✓	Storage temperature (T-T)	-15 - 45 °C
Ports & interfaces		Operating relative humidity (H-H)	0 - 95%
AC outlet types	C13 coupler, C19 coupler	Storage relative humidity (H-H)	0 - 95%
Power plug	Type F	Operating altitude	0 - 3000 m
AC outlets quantity	5 AC outlet(s)	Non-operating altitude	0 - 15240 m
USB port	✓	Technical details	
USB 2.0 ports quantity	2	Sustainability compliance	✓
USB port type	USB Type-A/USB Type-B	Sustainability certificates	Green Premium
Ethernet LAN (RJ-45) ports	1	Doesn't contain	Mercury
Emergency Power Off (EPO) connector	✓	Compliance certificates	CE, REACH, RoHS
Battery		Weight & dimensions	
Battery technology	Lithium-Ion (Li-Ion)	Width	432 mm
Battery capacity	336 VAh	Depth	560 mm
Battery voltage	50 V	Height	43 mm
Number of batteries supported	5	Weight	15.9 kg

Battery

Typical backup time at full load	6 min
Typical backup time at half load	14 min

Weight & dimensions

Package width	564 mm
Package depth	764 mm
Package height	27820 mm
Package weight	24.2 kg

Packaging data

Cables included	RJ-45
Management card included	✓



0731304573623



731304573623

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.