



APC SRTL10KRM4UI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 10 kVA 10000 W 12 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRTL10KRM4UI

Tuotteen nimi : SRTL10KRM4UI



APC SRTL10KRM4UI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 10 kVA, Lähtöteho: 10000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Hardwire, Virtapistoke: Hardwire, Ulostulojen määrä: 12 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion), Akun jännite: 180 V, Tyypillinen varmuuskopioaika täydellä kuormituksella: 5 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: Harmaa, Telineen kapasiteetti: 4U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 832 mm, Tuotteen korkeus: 175 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	11 min
Output power capacity *	10 kVA	Battery life (max)	10 year(s)
Output power *	10000 W	Battery recharge time	1.5 h
Waveform *	Sine	Design	
Input operation voltage (min) *	220 V	Form factor *	Rackmount/Tower
Input operation voltage (max) *	240 V	Rack capacity	4U
Input frequency *	40/70 Hz	Product colour *	Grey
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	✓
Output frequency	50/60 Hz	International Protection (IP) code	IP20
Surge energy rating	1410 J	Certification	EN/IEC 62040-1 EN/IEC 62040-2 IEC 62040-2
Heat dissipation	1900 BTU/h	Operational conditions	
Crest factor	3:1	Operating temperature (T-T)	0 - 40 °C
Output voltage Total Harmonic Distortion (THD)	5%	Storage temperature (T-T)	-15 - 45 °C
Noise level	55 dB	Operating relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 95%
Audible alarm modes	Alarm when on battery, Low battery alarm	Operating altitude	0 - 3000 m
Power source type	AC	Non-operating altitude	0 - 15240 m
Detachable power cord	✓	Technical details	
Ports & interfaces		Sustainability compliance	✓
AC outlet types	C13 coupler, C19 coupler, Hardwire	Sustainability certificates	Green Premium
Power plug	Hardwire	Compliance certificates	CE, REACH, UKCA, VDE
AC outlets quantity	12 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	432 mm
Emergency Power Off (EPO) connector	✓	Depth	832 mm
SmartSlot	✓	Height	175 mm

Battery		Weight & dimensions	
Battery technology	Lithium-Ion (Li-Ion)	Weight	55 kg
Battery voltage	180 V	Package width	650 mm
Typical backup time at full load	5 min	Package depth	1000 mm
		Package height	630 mm
		Package weight	88.5 kg
Packaging data			
		Rack mount kit	✓
		Cables included	USB cable
		Manual	✓



0731304578505



731304578505

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.