## QNAP TVS-H874T-I9-64G NAS- ja tallennuspalvelimet Tower Intel® Core™ i9 64 GB DDR4 0 TB QNAP QTS musta

Tuotemerkki : QNAP

Tuotekoodi: TVS-H874T-I9-64G

Tuotteen nimi : TVS-H874T-I9-64G

QNAP TVS-H874T-I9-64G. Malli: NAS. Alustatyyppi: Tower. Laitteen luokka: Koti & Kotitoimisto. Suoritinperhe: Intel® Core™ i9. Sisäinen muisti: 64 GB, Sisäisen muistin tyyppi: DDR4. Asennetun muistin kokonaiskapasiteetti: 0 TB. Käyttöjärjestelmä asennettu: QNAP QTS





	Design	
Serial ATA II, Serial ATA III 2.5,3.5,M.2 2 • 0, 1, 5, 6, 10, 50, 60, JBOD •	Fan diameter 2 LED indicators Built-in display Display type Cable lock slot Cable lock slot type	6 cm HDD, LAN, M.2, Status, USB ✓ LCD ✓ Kensington
<ul> <li>Image: A start of the start of</li></ul>	Performance	
<ul> <li>FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4</li> <li>X</li> <li>0 TB</li> <li>8</li> <li>X</li> <li>HDD &amp; SSD</li> </ul>	Type * Device class * Backup function * Backup features Buzzer Snapshot Management protocols Security algorithms	NAS Home & Home Office Cloud, iSCSI LUN SNMP V2, V3 256-bit AES, FIPS 140-2, SSH, TLS
<ul> <li>✓</li> </ul>	Access Control List (ACL)	<ul> <li>Image: A second s</li></ul>
Intel Intel® Core™ i9 16 24	Reset button On/off switch Built-in FTP server Browser supported System log	<ul> <li>Apple Safari, Google Chrome, Microsoft Edge, Mozilla Firefox</li> </ul>
Intel UHD Graphics 770	Hot spare	1
64 GB DDR4 64 GB 2	Disk scan S.M.A.R.T. support Share folder USB copy function	✓ Thick, Thin ✓
SO-DIMM	Software	
5000 MB ✓ 10,100,1000,2500 Mbit/s 10000 Mbit/s	Operating system installed * Operating system version Windows operating systems supported	QNAP QTS QTS 5.1.0 Windows 10, Windows 11, Windows 7, Windows 8
	2.5,3.5,M.2 2 ✓ 0, 1, 5, 6, 10, 50, 60, JBOD ✓ ✓ FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 × 0 TB 8 × HDD & SSD ✓ Intel Intel® Core™ i9 16 24 Intel UHD Graphics 770 G4 GB DDR4 64 GB 2 SO-DIMM 5000 MB ✓ Intel Intel Intel Intel Intel® Core™ i9 16 24 Intel Intel Inte	Serial ATA IIFan diameter 22.5,3.5,M.2LED indicators2Built-in display2Display type0, 1, 5, 6, 10, 50, 60, JBODCable lock slot2Cable lock slot2Type *FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4Backup features8SnapshotXBackup features9SonapshotXManagement protocols10SSD4Cacess Control List (ACL)11Cacess Control List (ACL)11Cacess Control List (ACL)11System log11Sanapshot2Sotement12Sotem log13Sanapshot2Sotem log14System log15Sanapshot2Sotem log16Smare supported24Share folder24Share folder25Sotem function26Sotem version27Sotem version28

Network		Software	
DHCP server iSCSI support	у У	Linux operating systems supported	CentOS 7.0, SuSE Linux 12.0, SuSE Linux 12.3, SuSE Linux 15, Ubuntu 14.04
Wake-on-LAN ready Supported network protocols Dynamic DNS (DDNS)	✓ IPv4, IPv6 ✓	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Ports & interfaces USB port *	<i>v</i>		
JSB 3.2 Gen 2 (3.1 Gen 2) Type-A 2 ports quantity JSB 3.2 Gen 2 (3.1 Gen 2) Type-C 1 ports quantity 1	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019	
HDMI ports quantity		Other operating systems supported	IBM AIX 7.1, IBM AIX 7.2, Solaris 10
HDMI version1.4bEthernet LAN (RJ-45) ports *2Concurrent connections3500PCI Express x16 (Gen 4.x) slots1		Power	
	3500	Power supply location Power supply unit (PSU) capacity	Built-in 350 W
Design		Number of power supply units	1 104.35 W
Chassis type * Cooling type * Product colour Number of fans Fan diameter	Tower Active Black 3 fan(s) 12 cm	Power consumption (typical) Power consumption (sleep) AC input voltage	62.668 W 100 - 240 V
		Weight & dimensions	
		Width * Depth * Height * Weight Package weight	329.3 mm 280.8 mm 188.2 mm 7.34 kg 8.99 kg
		Packaging content	
		Cables included Power cables quantity Number of screws	AC, LAN (RJ-45) 1 56

Operational conditions


Storage temperature (T-T)

Operating temperature (T-T)

Operating relative humidity (H-H) 5 - 95%

0 - 40 °C

-20 - 70 °C



## 4711103084465

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.