



Lenovo ThinkSystem ST650 V2 server Tower (4U) Intel Xeon Silver 4309Y 2.8 GHz 32 GB DDR4-SDRAM 750 W



Brand : Lenovo **Product family:** ThinkSystem **Product code:** 7Z74A030EA
Product name : ST650 V2

- No OS
- Intel Xeon Silver 4309Y (12MB Cache, 2.8GHz)
- 32GB (3200MHz) DDR4-SDRAM (1 x 32)
Intel Xeon Silver 4309Y (12MB Cache, 2.8GHz), 32GB DDR4-SDRAM (3200MHz), LAN (Broadcom 57416), 9350-8i, 750W, No OS
Lenovo ThinkSystem ST650 V2. Processor family: Intel Xeon Silver, Processor frequency: 2.8 GHz, Processor model: 4309Y. Internal memory: 32 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 32 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 750 W, Redundant power supply (RPS) support. Chassis type: Tower (4U)

Processor		Design	
Processor manufacturer *	Intel	Chassis type *	Tower (4U)
Processor family *	Intel Xeon Silver	Product colour	Black
Processor model *	4309Y	Rack mounting	✓
Processor frequency *	2.8 GHz	Performance	
Processor boost frequency	3.6 GHz	Performance management	XClarity Enterprise
Processor cache	12 MB	Trusted Platform Module (TPM)	✓
Number of processors installed	1	Trusted Platform Module (TPM) version	2.0
Memory		Software	
Internal memory *	32 GB	Operating system installed *	✗
Internal memory type *	DDR4-SDRAM	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
Memory clock speed	3200 MHz	Power	
Memory layout (slots x size)	1 x 32 GB	Redundant power supply (RPS) support *	✓
Storage		Power supply *	750 W
RAID support *	✓	Number of redundant power supplies installed	1
RAID levels	0, 1, 5, 6, 10, 50, 60	Operational conditions	
Supported RAID controllers	9350-8i	Operating temperature (T-T)	5 - 45 °C
Internal drive bays	8	Storage temperature (T-T)	-40 - 60 °C
Graphics		Operating relative humidity (H-H)	8 - 90%
Maximum graphics card memory	16 MB	Storage relative humidity (H-H)	8 - 90%
Network		Operating altitude	0 - 3050 m
LAN controller	Broadcom 57416	Weight & dimensions	
Ethernet LAN	✓	Width	175 mm
Cabling technology	10/100/1000Base-T(X)	Depth	734 mm
Ethernet interface type	10 Gigabit Ethernet	Height	462 mm
Ports & interfaces			
Ethernet LAN (RJ-45) ports *	3		
USB 2.0 ports quantity	1		
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	5		
VGA (D-Sub) ports quantity	1		
Serial ports quantity	1		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date