

ZYXEL

Zyxel XMG1915-10EP Hallittu L2 2.5G Ethernet (100/1000/2500) Power over Ethernet -tuki



Tuotemerkki : Zyxel

Tuotekoodi: XMG1915-10EP-EU0101F

Tuotteen nimi : XMG1915-10EP

Zyxel XMG1915-10EP. Kytkein tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 2.5G Ethernet (100/1000/2500), Basic kytchentä RJ-45 Ethernet-porttien määrä: 8. MAC-osoitetaulukko: 16000 entries, Kytchentäkapasiteetti: 80 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3bz,.... Power over Ethernet -tuki. Telineasennus

Management features		Design	
Switch type *	Managed	Rack mounting *	✓
Switch layer	L2	LED indicators	✓
Quality of Service (QoS) support	✓	Performance	
Ports & interfaces		Internal memory	256 MB
Basic switching RJ-45 Ethernet ports quantity *	8	Flash memory	32 MB
Basic switching RJ-45 Ethernet ports type *	2.5G Ethernet (100/1000/2500)	Firmware upgradeable	✓
SFP+ module slots quantity	2	Mean time between failures (MTBF)	394.499 h
Network		Power	
Networking standards *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3bz, IEEE 802.3x, IEEE 802.3z	Power source *	AC/PoE
10G support *	✓	Power supply included *	✓
VLAN support	✓	AC input voltage	100 - 240 V
Virtual LAN features	MAC address-based VLAN, Port-based VLAN, Voice VLAN	AC input frequency	50/60 Hz
Data transmission		Power consumption (max)	150 W
Switching capacity *	80 Gbit/s	Power over Ethernet (PoE)	
Forwarding rate	59.5 Mpps	Power over Ethernet (PoE) *	✓
MAC address table *	16000 entries	Power over Ethernet (PoE) ports quantity	8
Jumbo frames support	✓	Total Power over Ethernet (PoE) budget	130 W
Jumbo frames	12000	Operational conditions	
Packet buffer memory	1.5 MB	Operating temperature (T-T)	0 - 40 °C
Security		Storage temperature (T-T)	-40 - 70 °C
DHCP features	DHCP client, DHCP relay, DHCP snooping	Operating relative humidity (H-H)	5 - 95%
IGMP snooping	✓	Storage relative humidity (H-H)	5 - 95%
Security algorithms	SNMP, SNMPv2, SNMPv3	Weight & dimensions	
MAC address filtering	✓	Width	250 mm
SSH/SSL support	✓	Depth	104 mm
Authentication type	RADIUS	Height	27 mm
Multicast features		Weight	780 g
Multicast support	✓	Packaging content	
Multicast features	Multicast forwarding	Cables included	AC



4718937631452



0760559130312



760559130312

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.