

## Epson Expression 13000XL Pro Flatbed scanner 2400 x 4800 DPI A3 Grey, White



**Brand :** Epson

**Product code:** B11B257401BT

**Product name :** Expression 13000XL Pro

- High-quality A3 scanning
  - Dual light technology scanner
  - Advanced software features
- A3 film and graphics scanner

[Epson Expression 13000XL Pro Flatbed scanner 2400 x 4800 DPI A3 Grey, White:](#)

High-quality A3 film and graphics scanner for sharp and accurate capturing of plans, x-rays, film negatives, with the precision users demand.

The Expression 13000XL Pro is a high-resolution A3 scanner designed to meet the most demanding needs across a variety of industries including graphic design. Featuring 3.8 DMAx, dual light technology, auto focus, glare reduction, and the exceptional SilverFast Ai 9 image-processing functions, this scanner offers excellent image reproduction.

<b>Scanning</b>		<b>Power</b>	
Maximum scan size *	310 x 437 mm	Power supply type *	AC
Optical scanning resolution *	2400 x 4800 DPI	AC input frequency	50/60 Hz
Input colour depth	16 bit	Input voltage	100 - 240 V
Output colour depth	48 bit	<b>Weight &amp; dimensions</b>	
Film scanning	✓	Width	656 mm
Film scan speed (colour, low res)	12 sec/page	Depth	460 mm
<b>Design</b>		Height	292 mm
Scanner type *	Flatbed scanner	Weight	20.5 kg
Product colour *	Grey, White	<b>System requirements</b>	
Built-in display *	✗	Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1
<b>Performance</b>		Mac operating systems supported	Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma
Scan drivers	ICA, SANE, TWAIN, WIA	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012 x64
<b>Paper handling</b>		<b>Operational conditions</b>	
Maximum ISO A-series paper size *	A3	Operating temperature (T-T)	5 - 35 °C
ISO A-series sizes (A0...A9)	A3, A4, A5	Storage temperature (T-T)	25 - 60 °C
ISO B-series sizes (B0...B9)	B4, B5	Operating relative humidity (H-H)	10 - 80%
<b>Ports &amp; interfaces</b>		Storage relative humidity (H-H)	10 - 85%
USB port *	✓		
USB version	2.0		



8715946716992

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-NOV-2024. Prints or copies of Information are only valid on the printed Publication date