

DELL PowerEdge R660XS server 480 GB Rack (1U) Intel Xeon Silver 4410T 2.7 GHz 32 GB DDR5-SDRAM 700 W

Brand : DELL Product family: PowerEdge Product code: 9VV4D

Product name: R660XS




- No OS
- Intel Xeon Silver 4410T (26.25MB Cache, 2.7GHz)
- 32GB DDR5-SDRAM (1 x 32) & 480GB SSD
- iDRAC9, Enterprise 16G

Intel Xeon Silver 4410T (26.25MB Cache, 2.7GHz), 32GB DDR5-SDRAM, 480GB SSD, LAN (Broadcom 5720), PERC H755, iDRAC9, Enterprise 16G, $2 \times 700W$, No OS

DELL PowerEdge R660XS server 480 GB Rack (1U) Intel Xeon Silver 4410T 2.7 GHz 32 GB DDR5-SDRAM 700 W:

The perfect blend of performance and density

Run the most popular IT applications easily with this air-cooled server that is the best choice for balanced and dense compute.





Processor		Ports & interfaces	
Processor manufacturer * Processor family *	ocessor family * Intel Xeon Silver ocessor model * 4410T ocessor frequency * 2.7 GHz ocessor boost frequency 4 GHz ocessor cores 10 ocessor cache 26.25 MB	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Processor model *		Design	
Processor frequency * Processor boost frequency Processor cores Processor cache Number of processors installed		Chassis type * Product colour Rack rails Bezel	Rack (1U) Black ✓
Maximum internal memory	512 GB	Performance	
Memory Internal memory * 32 GB Internal memory type * DDR5-SDRAM Buffered memory type Registered (buffered) Memory ranking 2 Memory slots 16x DIMM Memory layout (slots x size) 1 x 32 GB Memory data transfer rate 5600 MT/s Maximum internal memory * 1 TB	Remote administration Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	iDRAC9, Enterprise 16G ✓ 2.0	
		Software	
	Operating system installed * Compatible operating systems *	X Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSAN/ESXi	
Storage		Power	
Total storage capacity * Number of SSDs installed	480 GB 1	Redundant power supply (RPS) support *	✓
SSD capacity	480 GB	Power supply *	700 W
SSD interface SSD size	SATA III 2.5"	Number of redundant power supplies supported	2
RAID support * Supported RAID controllers	✓ PERC H755	Number of redundant power supplies installed Power supply input voltage	2 200 - 240 V
Hot-Plug support	✓	Power cable length	2 m

Storage		Power	
Internal drive bays Supported storage drive interfaces Graphics	8 SAS, Serial ATA	Power cable connector 1 Power cable connector 2 Power cable current	C13 coupler C14 coupler 12 A
On-board graphics card	x	Operational conditions	
Network LAN controller Ethernet LAN Cabling technology	Broadcom 5720 ✓ 10/100/1000Base-T(X)	Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude	10 - 35 °C -40 - 65 °C 5 - 95% 0 - 3048 m 0 - 12000 m
Ethernet interface type	Gigabit Ethernet	Weight & dimensions	
Ports & interfaces Ethernet LAN (RJ-45) ports * 4 USB 2.0 ports quantity 2		Width Height	434 mm 42.8 mm
	2	Other features	
		Data transfer rate Bytes per sector	6 Gbit/s 512



5397184843468

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.