



DELL PowerEdge R660XS server 480 GB Rack (1U) Intel Xeon Silver 4410Y 2 GHz 32 GB DDR5-SDRAM 700 W

Brand : DELL

Product family: PowerEdge

Product code: 6JN0K

Product name : R660XS



- No OS

- Intel Xeon Silver 4410Y (30MB Cache, 2GHz)

- 32GB DDR5-SDRAM (1 x 32) & 480GB SSD

- iDRAC9, Enterprise 16G

Intel Xeon Silver 4410Y (30MB Cache, 2GHz), 32GB DDR5-SDRAM, 480GB SSD, LAN (Broadcom 5720),

PERC H755, iDRAC9, Enterprise 16G, 2 x 700W, No OS

[DELL PowerEdge R660XS server 480 GB Rack \(1U\) Intel Xeon Silver 4410Y 2 GHz 32 GB DDR5-SDRAM 700 W:](#)

The perfect blend of performance and density

Run the most popular IT applications easily with this air-cooled server that is the best choice for balanced and dense compute.

DELL PowerEdge R660XS. Processor family: Intel Xeon Silver, Processor frequency: 2 GHz, Processor model: 4410Y. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM, Memory layout (slots x size): 1 x 32 GB. Total storage capacity: 480 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 700 W, Redundant power supply (RPS) support. Chassis type: Rack (1U)



| Processor | | Ports & interfaces | |
|--|-----------------------|---|--|
| Processor manufacturer * | Intel | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 1 |
| Processor family * | Intel Xeon Silver | Design | |
| Processor model * | 4410Y | Chassis type * | Rack (1U) |
| Processor frequency * | 2 GHz | Product colour | Black |
| Processor boost frequency | 3.9 GHz | Rack rails | ✓ |
| Processor cores | 12 | Bezel | ✓ |
| Processor cache | 30 MB | Performance | |
| Number of processors installed | 1 | Remote administration | iDRAC9, Enterprise 16G |
| Thermal Design Power (TDP) | 150 W | Trusted Platform Module (TPM) | ✓ |
| Maximum internal memory supported by processor | 512 GB | Trusted Platform Module (TPM) version | 2.0 |
| Memory | | Software | |
| Internal memory * | 32 GB | Operating system installed * | ✗ |
| Internal memory type * | DDR5-SDRAM | Compatible operating systems * | Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSAN/ESXi |
| Buffered memory type | Registered (buffered) | Power | |
| Memory ranking | 2 | Redundant power supply (RPS) support * | ✓ |
| Memory slots | 16x DIMM | Power supply * | 700 W |
| Memory layout (slots x size) | 1 x 32 GB | Number of redundant power supplies supported | 2 |
| Memory data transfer rate | 5600 MT/s | Number of redundant power supplies installed | 2 |
| Maximum internal memory * | 1 TB | Power supply input voltage | 200 - 240 V |
| Storage | | Power cable length | 2 m |
| Total storage capacity * | 480 GB | | |
| Number of SSDs installed | 1 | | |
| SSD capacity | 480 GB | | |
| SSD interface | SATA III | | |
| SSD size | 2.5" | | |
| RAID support * | ✓ | | |
| Supported RAID controllers | PERC H755 | | |

| | | | |
|------------------------------------|----------------------|---------------------------------|-------------|
| Storage | | Power | |
| Hot-Plug support | ✓ | Power cable connector 1 | C13 coupler |
| Internal drive bays | 8 | Power cable connector 2 | C14 coupler |
| Supported storage drive interfaces | SAS, Serial ATA | Power cable current | 12 A |
| Graphics | | Operational conditions | |
| On-board graphics card | ✗ | Operating temperature (T-T) | 10 - 35 °C |
| Network | | Storage temperature (T-T) | -40 - 65 °C |
| LAN controller | Broadcom 5720 | Storage relative humidity (H-H) | 5 - 95% |
| Ethernet LAN | ✓ | Operating altitude | 0 - 3048 m |
| Cabling technology | 10/100/1000Base-T(X) | Non-operating altitude | 0 - 12000 m |
| Ethernet interface type | Gigabit Ethernet | Weight & dimensions | |
| Ports & interfaces | | Width | 434 mm |
| Ethernet LAN (RJ-45) ports * | 4 | Height | 42.8 mm |
| USB 2.0 ports quantity | 2 | Other features | |
| | | Data transfer rate | 6 Gbit/s |
| | | Bytes per sector | 512 |



5397184843451

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date