



APC SMTL2200RM12UC UPS-virtalähde Linjainteraktiivinen 2,2 kVA 1980 W 10 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMTL2200RM12UC

Tuotteen nimi : SMTL2200RM12UC



APC SMTL2200RM12UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Pistorasian tyypit: C13 liitin, C19 liitin, Ulostulojen määrä: 10 AC-pistorasia(a), Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Harmaa, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 683 mm, Tuotteen korkeus: 86 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	3 h
Output power capacity *	2.2 kVA	Hot-swap battery	✓
Output power *	1980 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	151 V		
Input operation voltage (max) *	302 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	375 J		
Response time	6 ms		
Heat dissipation	215 BTU/h		
Number of input phases	1		
Number of output phases	1		
Output voltage Total Harmonic Distortion (THD)	5%		
Noise level	55 dB		
Audible alarm(s)	✓		
Auto-restart	✓		
Power source type	AC		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler	Form factor *	Rackmount/Tower
AC outlets quantity	10 AC outlet(s)	Rack capacity	2U
Number of output IEC jumpers	3	Cable length	2 m
USB port	✓	Product colour *	Black, Grey
Serial interface	✓	Display type	LCD
		LED indicators	✓
		Certification	IRAM, RCM
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3048 m
		Non-operating altitude	0 - 15240 m
		Technical details	
		Sustainability compliance	✓
		Compliance certificates	CE, GS mark, RoHS, VDE
		Weight & dimensions	
		Width	432 mm
		Depth	683 mm
		Height	86 mm

Ports & interfaces		Weight & dimensions	
Serial interface type	RJ-45	Weight	42.3 kg
Ethernet LAN (RJ-45) ports	1	Package width	980 mm
SmartSlot	✓	Package depth	600 mm
Battery		Package height	254 mm
Battery technology	Sealed Lead Acid (VRLA)	Package weight	49.7 kg
Battery life (max)	5 year(s)	Packaging data	
		Rack mount kit	✓
		Cables included	USB cable
		Other features	
		Input connection type	BS1363A British, IEC 320 C20, Schuko CEE 7 / EU1-16P
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304643197



731304643197

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.