



APC SMTL3000RM12UC UPS-virtalähde Linjainteraktiivinen 3 kVA 2700 W 9 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMTL3000RM12UC

Tuotteen nimi : SMTL3000RM12UC



APC SMTL3000RM12UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 9 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion). Kotelo: Telineasennettava, Tuotteen väri: musta, Harmaa, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 683 mm, Tuotteen korkeus: 86 mm



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	3 kVA	Rack capacity	2U
Output power *	2700 W	Product colour *	Black, Grey
Waveform *	Sine	Control type	Touch
Input operation voltage (min) *	160 V	Display type	LCD
Input operation voltage (max) *	286 V	LED indicators	✓
Input frequency *	50/60 Hz	International Protection (IP) code	IP20
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Surge energy rating	739 J	Operating relative humidity (H-H)	0 - 95%
Response time	6 ms	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Operating altitude	0 - 3048 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 7620 m
Noise level	55 dB	Technical details	
Audible alarm(s)	✓	Sustainability compliance	✓
Auto-restart	✓	Compliance certificates	RoHS
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler, C19 coupler	Width	432 mm
Power plug	C20 coupler	Depth	683 mm
AC outlets quantity	9 AC outlet(s)	Height	86 mm
USB port	✓	Weight	33.3 kg
Serial interface	✓	Package width	600 mm
Serial ports quantity	1	Package depth	980 mm
Ethernet LAN (RJ-45) ports	1	Package height	458 mm
SmartSlot	✓	Package weight	41.5 kg

Battery		Packaging data	
Battery technology	Lithium-Ion (Li-Ion)	Rack mount kit	✓
Hot-swap battery	✓	Cables included	RJ-45, USB cable
Automatic battery test	✓	Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304643173



731304643173

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.