

APC SMTL3000RMI2UC UPS-virtalähde Linjainteraktiivinen 3 kVA 2700 W 9 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMTL3000RMI2UC

Tuotteen nimi : SMTL3000RMI2UC


APC SMTL3000RMI2UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 9 ACpistorasia(a). Akkuteknologia: Litiumioni (Li-Ion). Kotelo: Telineasennettava, Tuotteen väri: musta, Harmaa, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS





Features		Design	
UPS topology * Output power capacity * Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency *	tput power capacity *3 kVAtput power *2700 Wveform *Sineut operation voltage (min) *160 Vut operation voltage (max) *286 Vut frequency *50/60 Hztput operation voltage (min)220 Vtput operation voltage (max)240 Vtput frequency50/60 Hzrge energy rating739 Jsponse time6 msest factor3:1ergency Power Off (EPO)✓	Rack capacity Product colour * Control type Display type LED indicators International Protection (IP) code Operational conditions	2U Black, Grey Touch LCD ✓ IP20
Output operation voltage (min) Output operation voltage (max) Output frequency Surge energy rating Response time Crest factor Emergency Power Off (EPO) Noise level		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3048 m 0 - 7620 m
Audible alarm(s)		Compliance certificates	RoHS
Auto-restart Ports & interfaces AC outlet types	✓ C13 coupler, C19 coupler	Packaging content Rack mount kit Cables included	✔ RJ-45, USB cable
Power plug AC outlets quantity USB port	C20 coupler 9 AC outlet(s) 1 1 1	Sustainability Sustainability compliance Weight & dimensions	1
Serial interface Serial ports quantity Ethernet LAN (RJ-45) ports SmartSlot		Weight & dimensions Width Depth Height Weight	432 mm 683 mm 86 mm 33.3 kg

Battery		Packaging data	
Battery technology	Lithium-Ion (Li-Ion)	Package width	600 mm
Hot-swap battery	✓	Package depth	980 mm
Automatic battery test	1	Package height	458 mm
Design		Package weight	41.5 kg
		Other features	
Form factor *	Rackmount	Nominal output voltage	230 V
		Nominal input voltage	230 V





731304643173

0731304643173

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.