ASUS ZenBeam L2 dataprojektori Lähiprojektori 400 ANSI lumenia DLP 1080p (1920x1080) Laivasto

Tuotemerkki : ASUS Tuotekoodi: 90LJ00I5-B01070

Tuotteen nimi: ZenBeam L2

ASUS ZenBeam L2. Projektorin kirkkaus: 400 ANSI lumenia, Projektioteknologia: DLP, Projektorin oletusresoluutio: 1080p (1920x1080). Valonlähteen tyyppi: LED, Valonlähteen käyttöikä: 30000 h. Tarkennus: Auto, Zoomin malli: Kiinteä, Heittosuhde: 1.2:1. Tuetut grafiikan erottelutarkkuudet: 1920 x 1080 (HD 1080), 3840 x 2160. HDMI/liitäntätyyppi: Mikro





Projector		Features			
Projector brightness Supported aspect ratios Screen size compatibility * Projection distance Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio *	## Arrival of the distance in size compatibility * ## Arr	Noise level (economic mode) HDCP Preset modes Noise level * High Dynamic Range (HDR) supported High Dynamic Range (HDR) technology Video apps	28 dB Bright, Game, Standard, Theatre 30 dB High Dynamic Range 10 (HDR10) Netflix		
Number of colours		Multimedia			
Keystone correction, horizontal Keystone correction, vertical Colour gamut	-30 - 30° -40 - 40° 120%	Built-in speaker(s) * RMS rated power	√ 10 W		
Light source		Design			
Light source type * Service life of light source * Lens system	LED 30000 h	Market positioning * Product type * Product colour * Placement	Portable Short throw projector Navy Ceiling, Desktop, Tripod		
Focus *	Auto	Display			
Zoom type Throw ratio	Fixed 1.2:1	Built-in display *	×		
Offset	100%	Power			
Video Full HD * Supported graphics resolutions	✓ 1920 x 1080 (HD 1080), 3840 x 2160	Power source * Power consumption (standby) * Power consumption (max) Battery technology Battery life (max)	USB 0.5 W 90 W Lithium-lon (Li-lon) 3.5 h		
Ports & interfaces	Micro	Battery			
HDMI connector type	MICIO	Battery capacity	65 Wh		

& interfaces		Operational conditions	
B 2.0 ports quantity	2	Operating temperature (T-T)	0 - 40 °C
JSB 2.0 Type-A ports quantity	1	Operating relative humidity (H-H)	20 - 90%
JSB 2.0 Type-C ports quantity	1	Weight & dimensions	
leadphone outputs	1	Width	132 mm
IDMI ports quantity *	1	Depth	132 mm
OVI port *	×	Height	172 mm
etwork		Weight *	1.57 kg
thernet LAN *	×	Package width	210 mm
		Package depth	177 mm
orage		Package height	265 mm
Card reader integrated *	×	Package weight	2.8 kg





4711081970712

0195553970730



195553970730

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.