

StarTech.com HDMI-SPLITTER-4K60UP videohaaroitin 2x HDMI

Tuotemerkki : StarTech.com

Tuotekoodi: HDMI-SPLITTER-4K60UP

Tuotteen nimi : HDMI-SPLITTER-4K60UP

StarTech.com HDMI-SPLITTER-4K60UP. Videoportin tyyppi: HDMI, Video ulos: 2x HDMI.
Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Tuotteen väri: musta, Kotelon materiaali:
Akrylinitrilli-butadienistyreeni (ABS). AC-syöttöjännite: 100 - 240 V, Syöttöjännite: 0.3 A,
Ulostulojännite: 5 V. Tuotteen leveys: 55 mm, Tuotteen syvyys: 65 mm, Tuotteen korkeus: 19 mm.
Pakkauksen leveys: 190 mm, Pakkauksen syvyys: 145 mm, Pakkauksen korkeus: 30 mm



| | | | |
|------------------------------------|--|-----------------------------------|--------------------------------|
| Ports & interfaces | | Weight & dimensions | |
| Video port type * | HDMI | Depth | 65 mm |
| Video out * | 2x HDMI | Height | 19 mm |
| HDMI version | 2.0 | Weight | 92 g |
| Video ports quantity * | 2 | Packaging data | |
| Features | | Package width | 190 mm |
| Product colour | Black | Package depth | 145 mm |
| Housing material | Acrylonitrile butadiene styrene (ABS) | Package height | 30 mm |
| Maximum resolution * | 4096 x 2160 pixels | Package weight | 168 g |
| HD type | 4K Ultra HD | Packaging content | |
| Maximum operating distance | 5 m | Manual | ✓ |
| Maximum refresh rate | 60 Hz | Cables included | USB Type-A to Micro-USB Type-B |
| High Dynamic Range (HDR) supported | ✓ | Operational conditions | |
| Cable length | 0.5 m | Operating temperature (T-T) | 0 - 70 °C |
| Data transfer rate | 18 Gbit/s | Storage temperature (T-T) | -10 - 80 °C |
| HDCP | ✓ | Operating relative humidity (H-H) | 5 - 90% |
| Supported video modes | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p | Sustainability | |
| LED indicators | Power | Sustainability compliance | ✓ |
| Power | | Technical details | |
| AC input voltage | 100 - 240 V | Supported audio channels | 7.1 |
| Input current | 0.3 A | Compliance certificates | CE, RoHS |
| Output voltage | 5 V | Logistics data | |
| Output current | 1 A | Master (outer) case width | 630 mm |
| USB powered | ✓ | Master (outer) case length | 470 mm |
| Weight & dimensions | | Master (outer) case height | 220 mm |
| Width | 55 mm | Products per master (outer) case | 60 pc(s) |



0065030897556



065030897556

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date