

StarTech.com ST121HDBTE AV-signaalin jatkaja AV-lähetin ja -vastaanotin musta

Tuotemerkki : StarTech.com

Tuotekoodi: ST121HDBTE

Tuotteen nimi : ST121HDBTE

StarTech.com ST121HDBTE. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Tuetut kaapelityypit: Cat5e, Cat6. Yhteysteknologia: Langallinen. AC-syöttöjännite: 110 - 240 V, Käyttöjännite: 12 V, Syöttöjännite: 0.5 A. Tuotteen leveys: 67 mm, Tuotteen syvyys: 80 mm, Tuotteen korkeus: 25 mm. Pakkauksen leveys: 235 mm, Pakkauksen syvyys: 156 mm, Pakkauksen korkeus: 65 mm



Features		Power	
Type *	AV transmitter & receiver	Power plug type	Type M
Maximum resolution *	4096 x 2160 pixels	Operational conditions	
Cable types supported	Cat5e, Cat6	Operating temperature (T-T)	0 - 40 °C
Maximum transfer distance	70 m	Storage temperature (T-T)	-10 - 60 °C
Maximum refresh rate	60 Hz	Operating relative humidity (H-H)	0 - 80%
Audio system	Multichannel	Weight & dimensions	
Audio output channels	7.1 channels	Width	67 mm
LED indicators	Status	Depth	80 mm
Supported video modes	720p, 1080p	Height	25 mm
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1600 (WQXGA), 4096 x 2160	Weight	428 g
		Packaging data	
Cable length	0.1 m	Package width	235 mm
Material	Aluminium	Package depth	156 mm
Daisy chain	✗	Package height	65 mm
Mean time between failures (MTBF)	52000 h	Package weight	1.1 kg
Product colour	Black	Packaging content	
Certification	CE, FCC, HDBT, TAA	AC adapter included	✓
Ports & interfaces		Cables included	LAN (RJ-45)
Connectivity technology *	Wired	Included power plug types	AU, EU, NA, UK
RJ-45 input ports	1	Manual	✓
RJ-45 output ports	1	Mounting brackets included	✓
HDMI in	1	Grounding wire	✓
Number of HDMI outputs	1	Technical details	
DC-in jack	✓	Audio support	✓
Power		Compliance certificates	RoHS
AC input voltage	110 - 240 V		
Operating voltage	12 V		

Power		Logistics data	
Input current	0.5 A	Master (outer) case width	325 mm
Output current	1.5 A	Master (outer) case length	411 mm
Power consumption (typical)	3 W	Master (outer) case height	257 mm
		Products per master (outer) case	12 pc(s)



0065030851107



065030851107



0102213458064



102213458064

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.