

StarTech.com ST12MHDLAN2K AV-signaalin jatkaja AV-lähetin ja -vastaanotin musta

Tuotemerkki : StarTech.com

Tuotekoodi: ST12MHDLAN2K

Tuotteen nimi : ST12MHDLAN2K

StarTech.com ST12MHDLAN2K. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 1920 x 1080 pikseliä, Tuetut kaapelityypit: Cat5e, Cat6. Äänen sisääntulo: 2 x 3.5 mm, Äänen ulostulo: 2 x 3.5 mm. AC-syöttöjännite: 100 - 240 V, Käyttöjännite: 12 V, Syöttöjännite: 0.6 A. Tuotteen leveys: 118 mm, Tuotteen syvyys: 131 mm, Tuotteen korkeus: 31 mm. Pakkauksen leveys: 235 mm, Pakkauksen syvyys: 365 mm, Pakkauksen korkeus: 75 mm



Features		Operational conditions	
Type *	AV transmitter & receiver	Operating temperature (T-T)	0 - 40 °C
Maximum resolution *	1920 x 1080 pixels	Storage temperature (T-T)	-10 - 60 °C
Cable types supported	Cat5e, Cat6	Operating relative humidity (H-H)	0 - 80%
Maximum transfer distance	100 m	Weight & dimensions	
Maximum refresh rate	60 Hz	Width	118 mm
Audio output channels	7.1 channels	Depth	131 mm
LED indicators	Link, Network, Power, Status	Height	31 mm
Supported video modes	720p, 1080p	Weight	1.2 kg
Supported graphics resolutions	1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800, 1360 x 768 (WXGA), 1440 x 900, 1600 x 900, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)	Packaging data	
Rack mounting	✓	Package width	235 mm
Daisy chain	✓	Package depth	365 mm
Rubber feet	✓	Package height	75 mm
Product colour	Black	Package weight	2.3 kg
Ports & interfaces		Packaging content	
RJ-45 input ports	1	AC adapter included	✓
RJ-45 output ports	1	Cables included	LAN (RJ-45), Phone (RJ-11)
HDMI in	1	Included power plug types	ANZ, EU, JP, NA, UK, US
Number of HDMI outputs	1	Manual	✓
Audio input	2 x 3.5 mm	IR blaster included	✓
Audio output	2 x 3.5 mm	IR receiver included	✓
RJ-11 ports quantity	4	Mounting kit	✓
3.5 mm (1/8-inch) in	✓	Technical details	
3.5 mm (1/8-inch) out	✓	Sustainability compliance	✓
		Compliance certificates	CE, RoHS
		Logistics data	
		Master (outer) case width	385 mm

Power		Logistics data	
AC input voltage	100 - 240 V	Master (outer) case length	390 mm
Operating voltage	12 V	Master (outer) case height	270 mm
Input current	0.6 A	Products per master (outer) case	6 pc(s)
Output current	1.5 A		
Power consumption (typical)	10 W		
External power adapter	✓		
Power plug type	Type M		



0065030878456



065030878456

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.