



DELL PowerEdge R550 palvelin 480 GB Teline (2U) Intel® Xeon Silver 4309Y 2,8 GHz 16 GB DDR4-SDRAM 1100 W

Tuotemerkki : DELL

Tuoteperhe: PowerEdge

Tuotekoodi: KJN4Y

Tuotteen nimi : R550



DELL PowerEdge R550. Suoritinperhe: Intel® Xeon Silver, Prosessorin taajuus: 2,8 GHz, Prosessorimalli: 4309Y. Sisäinen muisti: 16 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 16 GB. Kokonaistallennuskapasiteetti: 480 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Teline (2U)



Processor		Design	
Processor manufacturer *	Intel	Bezel	✓
Processor family *	Intel Xeon Silver	Performance	
Processor generation	3rd Generation Intel® Xeon® Scalable	Remote administration	iDRAC9, Enterprise 15G
Processor model *	4309Y	Software	
Processor frequency *	2.8 GHz	Operating system installed *	✗
Processor boost frequency	3.6 GHz	Compatible operating systems *	
Efficient-core base frequency	0.0028 GHz	Canonical Ubuntu Server LTS Citrix Hypervisor Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi	
Performance-core base frequency	2.8 GHz	Power	
Processor cores	8	Redundant power supply (RPS) support *	✓
Processor cache	12 MB	Power supply *	1100 W
Number of processors installed	1	Number of redundant power supplies supported	2
System bus rate	10.4 GT/s	Number of redundant power supplies installed	2
Processor threads	16	Power supply input voltage	100 - 240 V
Maximum internal memory supported by processor	512 GB	Power cable length	2 m
Memory		Power cable connector 1	C13 coupler
Internal memory *	16 GB	Power cable connector 2	C14 coupler
Internal memory type *	DDR4-SDRAM	Power cable current	12 A
Buffered memory type	Registered (buffered)	Operational conditions	
Memory ranking	2	Operating temperature (T-T)	10 - 35 °C
Memory slots	16x DIMM	Storage temperature (T-T)	-40 - 65 °C
Memory clock speed	2933 MHz	Operating relative humidity (H-H)	8 - 80%
Memory layout (slots x size)	1 x 16 GB	Storage relative humidity (H-H)	5 - 95%
Memory data transfer rate	3200 MT/s	Operating altitude	0 - 3048 m
Maximum internal memory *	1 TB		
Storage			
Total storage capacity *	480 GB		
Number of SSDs installed	1		

Storage		Operational conditions	
SSD capacity	480 GB	Non-operating altitude	0 - 12000 m
SSD interface	SATA III	Carbon footprint	
SSD size	2.5"	Total carbon footprint (kg of CO2e)	8790
RAID support *	✓	Total carbon emissions, standard deviation (kg of CO2e)	4760
Supported RAID controllers	PERC H755	Carbon emissions, manufacturing (kg of CO2e)	1018
Hot-Plug support	✓	Carbon emissions, logistics (kg of CO2e)	162
Optical drive type *	✗	Carbon emissions, energy usage (kg of CO2e)	7580
Internal drive bays	8	Carbon emissions, end-of-life (kg of CO2e)	26
Supported storage drive interfaces	SAS, Serial ATA	Total carbon emissions, w/o use phase (kg of CO2e)	1206
Drive writes per day (DWPD)	1	PAIA version	1.3.2, 2022
Network		Weight & dimensions	
LAN controller	Broadcom 57412	Width	482 mm
Ethernet LAN	✓	Depth	721.7 mm
Cabling technology	10/100/1000Base-T(X)	Height	86.8 mm
Ethernet interface type	10 Gigabit Ethernet	Technical details	
Ports & interfaces		Supported storage drives form factor (internal)	3.5"
Ethernet LAN (RJ-45) ports *	2	Other features	
USB 2.0 ports quantity	2	Data transfer rate	6 Gbit/s
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Bytes per sector	512
VGA (D-Sub) ports quantity	2		
Design			
Chassis type *	Rack (2U)		
Product colour	Black		
Rack rails	✓		



5397184760734

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date