

DELL P2724DEB 68.6 cm (27") LCD 2560 x 1440 pixels Quad HD

Brand : DELL P2724DEB

Product name: P2724DEB

- 68.6cm (27") Quad HD 2560 x 1440 LED IPS

- 8ms, 16:9, 350cd/m², 1000:1

- USB, HDMI, DisplayPort

68.6cm (27") Quad HD 2560 x 1440 LED IPS, 16:9, 350cd/m², 16.78M, 8ms, 178°/178°, 1000:1

DELL P2724DEB 68.6 cm (27") LCD 2560 x 1440 pixels Quad HD:

Connect like you're there with a 27-inch QHD IPS display built for effortless collaboration. DELL P2724DEB. Display diagonal: 68.6 cm (27"), Display technology: LCD, Display resolution: 2560 x 1440 pixels. Megapixel (approx.): 4 MP, Maximum frame rate: 60 fps. RMS rated power: 10 W. Product colour: Black, Silver, Screen shape: Flat, Panel mounting interface: 100 x 100 mm. USB version: 3.2 Gen 1 (3.1 Gen 1), USB Power Delivery up to: 90 W





Display		Computer system	
Display diagonal * Display technology * Panel type LED backlight	pgy * LCD IPS ✓ on * 2560 x 1440 pixels ass 350 cd/m² Quad HD ×	Computer system * Windows operating systems supported Mac operating systems supported	Windows 10, Windows 11 MacOS
Display resolution *		Performance	
Display brightness HD type * Touchscreen *		On Screen Display (OSD) HDCP HDCP version	✓ ✓ 1.4
Native aspect ratio * Response time	16:9 8 ms	Power	
Contrast ratio (typical) Viewing angle, horizontal Viewing angle, vertical Display number of colours Pixel pitch Display diagonal (metric) Surface hardness Anti-glare screen Camera Built-in camera Megapixel (approx.)	tio (typical) 1000:1 gle, horizontal 178° gle, vertical 178° aber of colours 16.78 million colours 0.2331 x 0.2331 mm gonal (metric) 68.47 cm dness 3H creen ✓	Power consumption (typical) Power consumption (max) Power consumption (standby) AC input voltage AC input frequency Energy efficiency scale Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours * Power supply type Operational conditions	Internal
Maximum frame rate	60 fps	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Audio		Operating relative humidity (H-H)	10 - 80%
Built-in speaker(s) Number of built-in speakers RMS rated power	2 10 W	Storage relative humidity (H-H) Weight & dimensions	5 - 90% 611.8 mm
Design		Display width Display depth	59.6 mm
Product colour * Screen shape	Black, Silver Flat	Display height Display weight	415.8 mm 5.65 kg

Design		Weight & dimensions	
VESA mounting * Panel mounting interface Bezel width (bottom) Bezel width (side)	✓ 100 x 100 mm 1.72 cm 7.52 mm	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand)	611.8 mm 230 mm 440.8 mm 8.27 kg
Bezel width (top)	3.84 cm	Packaging data	
Height adjustment	✓	Package weight	11.3 kg
Height adjustment	15 cm		11.3 kg
Pivot	✓	Packaging content	
Pivot angle	-90 - 90°	Stand included	✓
Swivelling	✓	Remote control included	×
Swivel angle range	-45 - 45°	Stylus pen	×
Tilt angle range	-5 - 21°	Power adapter included	✓
Ports & interfaces		Cables included	DisplayPort, USB Type-A to USB Type-B, USB Type-C
HDMI ports quantity * HDMI version	1 1.4	Sustainability	
DVI port *	1.4 X	Sustainability certificates	ENERGY STAR, TCO
DisplayPorts quantity	1	Network	
USB ports quantity	6		✓
USB version	3.2 Gen 1 (3.1 Gen 1)	Ethernet LAN *	1
USB 2.0 Type-B ports quantity	1	Ethernet LAN (RJ-45) ports Wi-Fi *	×
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3	Technical details	^
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Compliance certificates	RoHS
Number of USB Type-B upstream		Carbon footprint	
ports quantity	1	Total carbon footprint (kg of CO2e)	604
Number of USB Type-C upstream ports quantity	1	Total carbon emissions, standard deviation (kg of CO2e)	157
USB Type-A downstream ports quantity	3	Carbon emissions, manufacturing (kg of CO2e)	334
USB Type-C downstream ports quantity	1	Carbon emissions, logistics (kg of CO2e)	58
Microphone in	✓	Carbon emissions, energy usage (kg	206
USB port *	✓	of CO2e)	200
USB Type-C DisplayPort Alternate Mode	✓	Carbon emissions, end-of-life (kg of CO2e)	7
USB Power Delivery (USB PD)	✓	Total carbon emissions, w/o use phase (kg of CO2e)	398
USB Power Delivery up to	90 W	PAIA version	1.3.2



5397184657065

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.