



# Lindy SDVoE Controller

**Brand :** Lindy

**Product code:** 38364

**Product name :** SDVoE Controller

- Controls both matrix, video wall and multi view configurations using WebGUI, TCP, RS-232, IR and GPIO
- Dual network ports, one for network control and one for multicast video distribution
- WebGUI provides the complete status of all connected transceivers (No.38365), including Enc/Dec status, IP address and video preview
- Supports PoE, I/O level output and voltage 5V or 12V
- 2 year warranty

SDVoE Controller

Lindy SDVoE Controller. Type: AV repeater, Maximum resolution: 3840 x 2160 pixels, Cable types supported: Cat6. Connectivity technology: Wired, USB connector type: Micro-USB. Power source type: DC, Operating voltage: 12 V, Output current: 1 A. Width: 204 mm, Depth: 98.5 mm, Height: 21.5 mm. Quantity per pack: 1 pc(s), Package width: 255 mm, Package depth: 157 mm



Features		Operational conditions	
Type *	AV repeater	Storage temperature (T-T)	-20 - 60 °C
Maximum resolution *	3840 x 2160 pixels	Operating relative humidity (H-H)	20 - 90%
Cable types supported	Cat6	Storage relative humidity (H-H)	20 - 90%
Maximum transfer distance	100 m	<b>Weight &amp; dimensions</b>	
Maximum refresh rate	60 Hz	Width	204 mm
Supported network protocols	IP	Depth	98.5 mm
Material	Metal	Height	21.5 mm
Product colour	Black	Weight	760 g
Ports & interfaces		Packaging data	
Connectivity technology *	Wired	Quantity per pack	1 pc(s)
Ethernet LAN	✓	Package width	255 mm
RJ-45 input ports	1	Package depth	157 mm
RJ-45 output ports	1	Package height	77 mm
USB ports quantity	1	Package weight	960 g
USB connector type	Micro-USB	Package type	Box
RS-232 input ports	2	<b>Packaging content</b>	
3.5 mm (1/8-inch) in	✓	AC adapter included	✓
3.5 mm (1/8-inch) out	✓	Cables included	IR
Remote (IR) input	1	Quick start guide	✓
Remote (IR) output	1	Mounting kit	✓
DC-in jack	✓	<b>Technical details</b>	
Power		Special features	API support, 4 channel GPIO control ports (5V/12V optional level)
Power source type	DC	Sustainability compliance	✓
Operating voltage	12 V	Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
Output current	1 A		
Operational conditions			
Operating temperature (T-T)	0 - 40 °C		



4002888383646

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date