



BenQ RP6504 Interaktiivinen valkotaulu 165,1 cm (65") 3840 x 2160 pikseliä Kosketusnäyttö musta

Tuotemerkki : BenQ

Tuotekoodi: 9H.F97TC.DE1

Tuotteen nimi : RP6504



BenQ RP6504. Näytön halkaisija: 165,1 cm (65"), Työskentelyalue: 1428,5 x 803,5 mm, Näytön kirkkaus: 450 cd/m². Käyttöjärjestelmä asennettu: Android, Suoritinarkkitehtuuri: ARM Cortex A78 + ARM Cortex A55, Käyttäjän muisti: 64 GB. Kaiuttimen teho: 20 W, Subwooferin RMS-teho: 16 W. Ethernet LAN - datanopeudet: 10,100,1000 Mbit/s. USB-liitin: USB A-tyyppi, USB B-tyyppi, USB Type-C, DisplayPort versio: 1.2a, Mikrofoni: 3,5 mm

| Display | | Ports & interfaces | |
|------------------------------------|---------------------------------|-----------------------------------|--------------|
| Display diagonal * | 165.1 cm (65") | DisplayPort version | 1.2a |
| Display brightness | 450 cd/m ² | DisplayPorts quantity | 1 |
| Display resolution | 3840 x 2160 pixels | Ethernet LAN (RJ-45) ports | 1 |
| Anti-glare screen | ✓ | VGA (D-Sub) ports quantity | 1 |
| HD type | 4K Ultra HD | Line-in | ✓ |
| Panel type | IPS | Line-out | ✓ |
| Native aspect ratio | 16:9 | OPS slot | 1 |
| Contrast ratio (typical) | 1200:1 | S/PDIF out port | ✓ |
| Contrast ratio (dynamic) | 50000:1 | Microphone connectivity | 3.5 mm |
| Response time | 8 ms | Headphone connectivity | 3.5 mm |
| Touchscreen * | ✓ | Audio output | 3 |
| Touch technology | Multi-touch | Ergonomics | |
| Touchscreen type | Infrared | Product colour | Black |
| Number of simultaneous touchpoints | 50 | VESA mounting | ✓ |
| Touch system response time | 5 ms | Panel mounting interface | 600 x 400 mm |
| Colour gamut | 72% | Wall mountable | ✓ |
| Working area * | 1428.5 x 803.5 mm | Performance | |
| Surface material | Tempered glass | Humidity sensor | ✓ |
| Low Blue Light technology | ✓ | Temperature sensor | ✓ |
| Hardness | 9H | PM2.5 sensor | ✓ |
| Computer system | | Number of air ionizers | 1 |
| Operating system installed | Android | Motion sensor | ✓ |
| Operating system version | 13 | Power | |
| Built-in processor | ✓ | Power consumption (typical) | 95 W |
| Processor architecture | ARM Cortex A78 + ARM Cortex A55 | Power consumption (standby) | 0.5 W |
| Processor cores | 4 | AC input voltage | 100-240 V |
| User memory | 64 GB | AC input frequency | 50/60 Hz |
| RAM capacity | 8 GB | System requirements | |
| Graphics card family | ARM | Security updates end date | 30/11/2026 |
| Graphics card | Mali-G57 MC5 | Operational conditions | |
| Audio | | Operating temperature (T-T) | 0 - 40 °C |
| Built-in speaker(s) * | ✓ | Operating relative humidity (H-H) | 10 - 90% |
| Number of built-in speakers | 2 | Storage temperature (T-T) | -20 - 60 °C |
| Speaker power | 20 W | Storage relative humidity (H-H) | 10 - 90% |
| Built-in subwoofer | ✓ | Weight & dimensions | |
| Subwoofer RMS power | 16 W | | |
| Built-in microphone | ✓ | | |

| Network | | Weight & dimensions | |
|--|------------------------------------|------------------------------|-----------------------------------|
| Wi-Fi | ✓ | Width * | 1488.4 mm |
| Bluetooth | ✓ | Depth | 117.7 mm |
| Bluetooth version | 5.2 | Height * | 937.6 mm |
| Ethernet LAN | ✓ | Weight | 41 kg |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Packaging data | |
| Near Field Communication (NFC) | ✓ | Package width | 210 mm |
| Ports & interfaces | | Package depth | 1630 mm |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 7 | Package height | 1020 mm |
| Interface module USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity | 3 | Package weight | 48 kg |
| USB 2.0 ports quantity | 1 | Quantity per pack | 1 pc(s) |
| USB connector type | USB Type-A, USB Type-B, USB Type-C | Packaging content | |
| USB 2.0 Type-B Touch ports quantity | 3 | Pen tray included | ✓ |
| HDMI ports quantity | 5 | Cables included | HDMI, Power, USB, USB Type-C, VGA |
| USB Type-C ports quantity | 4 | Remote control included | ✓ |
| HDMI version | 2.0 | Mounting kit | ✓ |
| HDMI output ports quantity | 1 | Stylus included | ✓ |
| | | Number of stylus pens | 2 |
| | | Other features | |
| | | Country of origin | China |
| | | Logistics data | |
| | | Customs product code (TARIC) | 8528521000 |
| | | Products per pallet | 5 pc(s) |



4718755092459



8717472600295



0840046049133



840046049133

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.