

Samsung Galaxy Tab A9+ 5G LTE-TDD & LTE-FDD 64 GB 27.9 cm (11") 4 GB Wi-Fi 5 (802.11ac) Graphite

Brand : Samsung

Product code: SM-X216BZAAEUB

Product name : Galaxy Tab A9+ 5G



- 11" display with smooth 90Hz refresh rate
- Thin and light design
- Quad speakers with Dolby Atmos

SM-X216BZAAEUB

Samsung Galaxy Tab A9+ 5G. Display diagonal: 27.9 cm (11"), Display resolution: 1920 x 1200 pixels. Internal storage capacity: 64 GB. Internal memory: 4 GB. Rear camera resolution (numeric): 8 MP, Rear camera type: Single camera, Front camera resolution (numeric): 5 MP, Front camera. Top Wi-Fi standard: Wi-Fi 5 (802.11ac). Assisted GPS (A-GPS). Card reader integrated. Weight: 491 g. Product colour: Graphite



Display		Network	
Display diagonal *	27.9 cm (11")	Wi-Fi Direct	✓
Display resolution *	1920 x 1200 pixels	3G bands supported	850,900,1900,2100 MHz
Panel type	TFT	4G bands supported	700,800,850,900,1800,1900,2100,2300,2500,2600 MHz
HD type	WUXGA	5G bands supported	700,800,850,900,1800,2100,2300,2600,3500,3700 MHz
Display number of colours	16 million colours	Ports & interfaces	
Processor		USB 2.0 ports quantity	1
Processor cores	8	Headphone connectivity	3.5 mm
Memory		Phone features	
Internal memory *	4 GB	Voice call	✓
Storage		Video call	✓
Internal storage capacity *	64 GB	Design	
Card reader integrated *	✓	Device type *	Mobile tablet
Compatible memory cards	MicroSD (TransFlash)	Form factor *	Slate
Maximum memory card size	1 TB	Product colour *	Graphite
Camera		Performance	
Rear camera type *	Single camera	Assisted GPS (A-GPS) *	✓
Rear camera resolution (numeric) *	8 MP	GLONASS	✓
Auto focus	✓	BeiDou	✓
Maximum video resolution	1920 x 1080 pixels	GPS (satellite)	✓
Video capturing speed	30 fps	Galileo	✓
Front camera *	✓	Quasi-Zenith Satellite System (QZSS)	✓
Front camera resolution (numeric)	5 MP	Ambient light sensor	✓
Network		Gyroscope	✓
Mobile network generation	5G	Hall sensor	✓
Mobile network connection *	✓	Position location *	✓
3G standards	UMTS	Software	
4G standard	LTE-TDD & LTE-FDD	Platform *	Android
5G standard	Sub6 FDD, Sub6 TDD		
Bluetooth	✓		
Bluetooth version	5.1		

Network		Battery	
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Battery capacity *	7040 mAh
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Weight & dimensions	
		Width	257.1 mm
		Depth	6.9 mm
		Height	168.7 mm
		Weight	491 g



8806095360720

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-NOV-2024. Prints or copies of Information are only valid on the printed Publication date