

## Samsung Galaxy Tab A9+ 5G LTE-TDD & LTE-FDD 64 GB 27,9 cm (11") 4 GB Wi-Fi 5 (802.11ac) Grafiitti

**Tuotemerkki :** Samsung

**Tuotekoodi:** SM-X216BZAAEUB

**Tuotteen nimi :** Galaxy Tab A9+ 5G

Samsung Galaxy Tab A9+ 5G. Näytön halkaisija: 27,9 cm (11"), Näytön erottelutarkkuus: 1920 x 1200 pikseliä. Sisäinen tallennuskapasiteetti: 64 GB. Sisäinen muisti: 4 GB. Takakameran resoluutio (numeerinen): 8 MP, Takakameran tyyppi: Yksi kamera, Etukameran resoluutio (numeerinen): 5 MP, Etukamera. Wi-Fi-standardi: Wi-Fi 5 (802.11ac). Assisted GPS (A-GPS). Integroitu kortinlukija. Paino: 491 g. Tuotteen väri: Grafiitti



<b>Display</b>		<b>Network</b>	
Display diagonal *	27.9 cm (11")	Wi-Fi Direct	✓
Display resolution *	1920 x 1200 pixels	3G bands supported	850,900,1900,2100 MHz
Panel type	TFT	4G bands supported	700,800,850,900,1800,1900,2100,2300,2500,2600 MHz
HD type	WUXGA	5G bands supported	700,800,850,900,1800,2100,2300,2600,3500,3700 MHz
Display number of colours	16 million colours	<b>Ports &amp; interfaces</b>	
<b>Processor</b>		USB 2.0 ports quantity	1
Processor cores	8	Headphone connectivity	3.5 mm
<b>Memory</b>		<b>Phone features</b>	
Internal memory *	4 GB	Voice call	✓
<b>Storage</b>		Video call	✓
Internal storage capacity *	64 GB	<b>Design</b>	
Card reader integrated *	✓	Device type *	Mobile tablet
Compatible memory cards	MicroSD (TransFlash)	Form factor *	Slate
Maximum memory card size	1 TB	Product colour *	Graphite
<b>Camera</b>		<b>Performance</b>	
Rear camera type *	Single camera	Assisted GPS (A-GPS) *	✓
Rear camera resolution (numeric) *	8 MP	GLONASS	✓
Auto focus	✓	BeiDou	✓
Maximum video resolution	1920 x 1080 pixels	GPS (satellite)	✓
Video capturing speed	30 fps	Galileo	✓
Front camera *	✓	Quasi-Zenith Satellite System (QZSS)	✓
Front camera resolution (numeric)	5 MP	Ambient light sensor	✓
<b>Network</b>		Gyroscope	✓
Mobile network generation	5G	Hall sensor	✓
Mobile network connection *	✓	Position location *	✓
3G standards	UMTS	<b>Software</b>	
4G standard	LTE-TDD & LTE-FDD	Platform *	Android
5G standard	Sub6 FDD, Sub6 TDD		
Bluetooth	✓		
Bluetooth version	5.1		

Network		Battery	
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Battery capacity *	7040 mAh
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Weight & dimensions	
		Width	257.1 mm
		Depth	6.9 mm
		Height	168.7 mm
		Weight	491 g



8806095360720

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-NOV-2024. Prints or copies of Information are only valid on the printed Publication date