## Lindy 0.5m Cat.6A U/UTP Ultra Slim Network Cable, Grey

## Brand : Lindy

Product code: 47581

Product name : 0.5m Cat.6A U/UTP Ultra Slim Network Cable, Grey

0.5m Cat.6A U/UTP Ultra Slim Network Cable, Grey

Lindy 0.5m Cat.6A U/UTP Ultra Slim Network Cable, Grey:

Cat.6A U/UTP Ultra slim network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10GBase-T.

Cat 6A cable, for operating frequencies up to 500MHz, unshielded with single twisted pair (U/UTP). Designed as ultra slim cable for use in environments with restricted or limited installation space. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The very flexible and thin cable construction allows the cables to be installed in restricted or limited spaces such as server rooms or network hubs.

Available lengths: 0.3m, 1m, 1.5m, 2m, 3m, 5m.

Features		Features	
Product colour * Cable length * Cable standard * Cable shielding * Connector 1 * Connector 2 *	Grey 0.5 m Cat6a U/UTP (UTP) RJ-45 RJ-45	AWG wire size Frequency Bend radius (min) <b>Operational conditions</b> Operating temperature (T-T)	28 500 MHz 6 cm -10 - 60 °C
Connector 1 gender *MaleConnector 2 gender *MaleConnector 2 gender *MaleConnector 1 form factorStraightConnector 2 form factorStraightConnector contacts platingNickelConnector shielding✓Connector shield materialAluminiumJacket materialPolyvinyl chloride (PVC)Conductor materialCopper	Storage temperature (T-T) Weight & dimensions Width Depth	-10 - 40 °C 11 mm 28 mm	
	✓ Aluminium Polyvinyl chloride (PVC)	Height Outer diameter <b>Packaging data</b> Package type	6 mm 3.6 mm Polybag
		Technical details Sustainability compliance Compliance certificates	✓ REACH, RoHS







4002888475815

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.