

MPN: MO-10056H

SFP 1.25 Gbps, SMF, 20 km, LC, DOM support, Compatible with Extreme networks 10056H

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- ****100% Extreme Networks Compatible****



Specifications

Features	Brand compatibility	Extreme Networks
	Certification	MSA
	Compatible products	Extreme networks 10056H
	Easy to install	Y
	Form factor	SFP
	Plug and Play	Y
	RoHS compliance	Y
Operational conditions	Operating temperature (T-T)	0-70 °C
Package dimensions	Depth (package,cm)	10 cm
	Gross Weight (Package, kg)	0.03 kg
	Height (package,cm)	3 cm
	Width (package,cm)	6 cm
Performance	Ethernet interface type	Gigabit Ethernet
	Fiber cable diameters supported (core/cladding)	9/125 μm
	Fiber ethernet cabling technology	1000BASE-BX
	Fiber optic connector	SFP
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	20000 m
	Multi-mode fiber (MMF) supported	N
	Rx wavelength (max)	1310 nm
	SFP transceiver standard	BX-D
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Y

Performance	Tx wavelength (max)	1490 nm
Product dimensions	Net Weight (Product, kg)	0.02 kg
	Product Depth	5.6 cm
	Product Height	1.6 cm
	Product Width	2 cm
Vendor information	Brand Name	MicroOptics
	Warranty	3 Year(s)

Other images

