SFP 155 Mbps, SMF, 2 km, LC, DDMI, Compatible with Extreme Networks 10067

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Extreme Networks Compatible**

Specifications

Features		
	Brand compatibility	Extreme Networks
	Certification	MSA
	Compatible products	Extreme Networks 10067
	Easy to install	Y
	Form factor	SFP
	Hot-Plug support	Y
	Plug and Play	Y
	RoHS compliance	Y
Operational conditions	**Operating relative humidity (H-H)**	10 - 80 %
	Operating temperature (T-T)	0 - 70 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Package dimensions	**Gross Weight (Package, kg)**	0.04 kg
Packaging data	**Number of products included**	1 pc(s)
Performance	**Auto MDI/MDI-X**	Y
	Cabling technology	100BASE-FX
	Digital Diagnostics Monitoring (DDM)	Y
	Fiber optic connector	LC
	Fiber ports quantity	1
	Interface type	SFP
	Maximum data transfer rate	155 Mbit/s
	Maximum transfer distance	2000 m
	Multi-mode fiber (MMF) supported	Y

Performance		
	SFP transceiver standard	FX
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	N
	Wavelength	1310 nm

Product dimensions		
	Net Weight (Product, kg)	0.03 kg
	Product Depth	5.65 cm
	Product Height	0.85 cm
	Product Width	1.34 cm

Vendor information		
	Brand Name	MicroOptics
	Warranty	3 Year(s)

Other images