

MPN: MO-10122

XFP 10 Gbps, MMF, 300m, LC Duplex, DDMI support, Compatible with Extreme networks 10122

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- ****100% Extreme networks Compatible****



Specifications

Features	Brand compatibility	Extreme Networks
	Certification	MSA
	Compatible products	Extreme networks 10122
	Easy to install	Y
	Form factor	XFP
	Hot-Plug support	Y
	Plug and Play	Y
	RoHS compliance	Y
Operational conditions	Operating temperature (T-T)	0-70 °C
Package dimensions	Depth (package,cm)	10 cm
	Gross Weight (Package, kg)	0.03 kg
	Height (package,cm)	3 cm
	Width (package,cm)	6 cm
Performance	Ethernet interface type	10 Gigabit Ethernet
	Fiber cable diameters supported (core/cladding)	9/125 µm
	Fiber optic connector	XFP
	Maximum data transfer rate	10000 Mbit/s
	Maximum transfer distance	10000 m
	Multi-mode fiber (MMF) supported	N
	SFP transceiver standard	LR
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Y
	Wavelength	1310 nm

Product dimensions

Net Weight (Product, kg)	0.02 kg
Product Depth	5.6 cm
Product Height	1.6 cm
Product Width	2 cm

Vendor information

Brand Name	MicroOptics
Warranty	3 Year(s)

Other images

