

MPN: MO-DEM312GT2

# SFP 1.25 Gbps, MMF, 2 km, LC, Compatible with D-Link DEM312GT2

- **\*\*100% D-Link Compatible\*\***



## Specifications

Features	Certification	MSA
	Compatible products	D-Link DEM312GT2
	Easy to install	Yes
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	Operating temperature (T-T)	-45 - 75 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Package dimensions	Gross Weight (Package, kg)	0.04 kg
Packaging data	Number of products included	1 kusů
Performance	Digital Diagnostics Monitoring (DDM)	Yes
	Duplex system	Full
	Fiber ports quantity	1
	Interface type	SFP
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	2000 m
	Multi-mode fiber (MMF) supported	Yes
	SFP transceiver standard	SX
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	No
	Wavelength	1310 nm
Product dimensions	Net Weight (Product, kg)	0.03 kg
Vendor information	Brand Name	Lanview

Vendor information

Warranty

3 Year(s)

## Recommended accessories



**Lanview LC-LC Singlemode fibre cable duplex 3m OS2 9/125 LSZH**  
MPN: LVO231408



**Lanview LC-LC Singlemode fibre cable duplex 1m OS2 9/125 LSZH**  
MPN: LVO231406



**Lanview LC-LC Singlemode fibre cable duplex 2m OS2 9/125 LSZH**  
MPN: LVO231407



**MicroConnect Optical Fibre Cable, LC-LC, Singlemode, Duplex, OS2 (Yellow) 1.5m**  
MPN: FIB4410015



**MicroConnect Optical Fibre Cable, LC-LC, Singlemode, Duplex, OS2 (Yellow) 1m**  
MPN: FIB441001



**MicroConnect Optical Fibre Cable, LC-LC, Singlemode, Duplex, OS2 (Yellow) 3m**  
MPN: FIB441003