

MPN: MO-MGBIC-BX40-U

# SFP 1.25 Gbps, SMF, 40 km, LC, DOM support, Compatible with Extreme networks MGBIC-BX40-U

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **\*\*100% Extreme Networks Compatible\*\***



## Specifications

Features	Brand compatibility	Extreme Networks
	Certification	MSA
	Compatible products	Extreme networks MGBIC-BX40-U
	Easy to install	Y
	Form factor	SFP
	Plug and Play	Y
	RoHS compliance	Y
Operational conditions	Operating temperature (T-T)	0-70 °C
Package dimensions	Depth (package,cm)	10 cm
	Gross Weight (Package, kg)	0.03 kg
	Height (package,cm)	3 cm
	Width (package,cm)	6 cm
Performance	Cabling technology	1000BASE-BX10-U
	Ethernet interface type	Gigabit Ethernet
	Fiber cable diameters supported (core/cladding)	9/125 μm
	Fiber ethernet cabling technology	1000BASE-BX
	Fiber optic connector	SFP
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	40000 m
	Rx wavelength (max)	1310 nm
	SFP transceiver standard	BX-D
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Y

<b>Performance</b>	<b>Tx wavelength (max)</b>	1490 nm
<b>Product dimensions</b>	<b>Net Weight (Product, kg)</b>	0.02 kg
	<b>Product Depth</b>	5.6 cm
	<b>Product Height</b>	1.6 cm
	<b>Product Width</b>	2 cm
<b>Vendor information</b>	<b>Brand Name</b>	MicroOptics
	<b>Warranty</b>	3 Year(s)

## Other images

